

# Journal of Visualized Experiments

## Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating --Manuscript Draft--

<b>Manuscript Number:</b>	JoVE54088R3
<b>Full Title:</b>	Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating
<b>Article Type:</b>	Invited Methods Article - JoVE Produced Video
<b>Keywords:</b>	Biomass Conversion; Hot-Vapor-Filtration; Fast pyrolysis; catalytic hydrotreating; bio-oil; bio-fuel.
<b>Manuscript Classifications:</b>	92.23.3: chemical processing (general); 92.28.22: fuels; 92.28.35: liquid fuels; 92.28.5: catalysts (propellants)
<b>Corresponding Author:</b>	Huamin Wang Pacific Northwest National Laboratory Richland, WA UNITED STATES
<b>Corresponding Author Secondary Information:</b>	
<b>Corresponding Author E-Mail:</b>	Huamin.Wang@pnnl.gov
<b>Corresponding Author's Institution:</b>	Pacific Northwest National Laboratory
<b>Corresponding Author's Secondary Institution:</b>	
<b>First Author:</b>	Huamin Wang
<b>First Author Secondary Information:</b>	
<b>Other Authors:</b>	Douglas C Elliott Richard J French Steve Deutch Kristiina Iisa
<b>Order of Authors Secondary Information:</b>	
<b>Abstract:</b>	Lignocellulosic biomass conversion to produce biofuels has received significant attention because of the quest for a replacement for fossil fuels. Among the various thermochemical and biochemical routes, fast pyrolysis followed by catalytic hydrotreating is considered to be a promising near-term opportunity. This paper reports on experimental methods used 1) at the National Renewable Energy Laboratory (NREL) for fast pyrolysis of lignocellulosic biomass to produce bio-oils in a fluidized-bed reactor and 2) at Pacific Northwest National Laboratory (PNNL) for catalytic hydrotreating of bio-oils in a two-stage, fixed-bed, continuous-flow catalytic reactor. The configurations of the reactor systems, the operating procedures, and the processing and analysis of feedstocks, bio-oils, and biofuels are described in detail in this paper. We also demonstrate hot-vapor filtration during fast pyrolysis to remove fine char particles and inorganic contaminants from bio-oil. Representative results showed successful conversion of biomass feedstocks to fuel-range hydrocarbon biofuels and, specifically, the effect of hot-vapor filtration on bio-oil production and upgrading. The protocols provided in this report could help to generate rigorous and reliable data for biomass pyrolysis and bio-oil hydrotreating research.
<b>Author Comments:</b>	Dear Sir/Madam,  We are submitting our manuscript titled, "Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating" for publication in the Journal of Visualized Experiments. It has been extensively revised to

	<p>address comments from the editor, Dr. Nam Nguyen. A reply to comments is also submitted.</p> <p>This manuscript reports the experimental methods utilized in the National Renewable Energy Laboratory (NREL) for fast pyrolysis of lignocellulosic biomass to produce bio-oils in a fluidized-bed reactor with hot-vapor-filtration and those in the Pacific Northwest National Laboratory (PNNL) for the catalytic hydrotreating of bio-oils in a two-stage fixed bed continuous flow catalytic reactor. The configurations of the reactor systems, the operating procedures, and the processing and analysis of feedstocks, bio-oils, and bio-fuels are described in detail. Representative results showed the successful conversion of biomass feedstocks to fuel range hydrocarbon biofuels and, specifically, the effect of hot-vapor-filtration on the bio-oil production and upgrading. The JoVE's unique multimedia format could present this protocol clearly and accurately and therefore help the researcher to generate rigorous and reliable data for the biomass pyrolysis and bio-oil hydrotreating.</p> <p>Authors Huamin Wang and Douglas C Elliott from PNNL contribute to the PNNL's hydrotreating process and authors Richard J. French, Steve Deutch, and Kristiina Iisa from NREL contribute to NREL's fast pyrolysis process.</p> <p>Mr. Paul Yao and Ms. Molly Cummings have assisted us in the manuscript submission process.</p>
<b>Additional Information:</b>	
<b>Question</b>	<b>Response</b>
If this article needs to be "in-press" by a certain date to satisfy grant requirements, please indicate the date below and explain in your cover letter.	

**TITLE:**

Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor Filtered Fast Pyrolysis and Catalytic Hydrotreating

**AUTHORS:**

Wang, Huamin

Chemical and Biological Process Development  
Pacific Northwest National Laboratory (PNNL)  
Richland, Washington, USA  
huamin.wang@pnnl.gov

Elliott, Douglas C.

Chemical and Biological Process Development  
Pacific Northwest National Laboratory (PNNL)  
Richland, Washington, USA  
doug.elliott@pnnl.gov

French, Richard J.

National Bioenergy Center  
National Renewable Energy Laboratory (NREL)  
Golden, Colorado, USA  
Richard.French@nrel.gov

Deutch, Steve

National Bioenergy Center  
National Renewable Energy Laboratory (NREL)  
Golden, Colorado, USA  
Steve.Deutch@nrel.gov

Lisa, Kristiina

National Bioenergy Center  
National Renewable Energy Laboratory (NREL)  
Golden, Colorado, USA  
Kristiina.lisa@nrel.gov

**CORRESPONDING AUTHOR:**

Wang, Huamin

huamin.wang@pnnl.gov  
509-371-6705

**KEYWORDS:**

biomass conversion, hot-vapor filtration, fast pyrolysis, catalytic hydrotreating, bio-oil, bio-fuel

**SHORT ABSTRACT:**

Experimental methods for fast pyrolysis of lignocellulosic biomass to produce bio-oils and for the catalytic hydrotreating of bio-oils to produce fuel range hydrocarbons are presented. Hot-vapor filtration during fast pyrolysis to remove fine char particles and inorganic contaminants from bio-oil was also assessed.

**LONG ABSTRACT:**

Lignocellulosic biomass conversion to produce biofuels has received significant attention because of the quest for a replacement for fossil fuels. Among the various thermochemical and biochemical routes, fast pyrolysis followed by catalytic hydrotreating is considered to be a promising near-term opportunity. This paper reports on experimental methods used 1) at the National Renewable Energy Laboratory (NREL) for fast pyrolysis of lignocellulosic biomass to produce bio-oils in a fluidized-bed reactor and 2) at Pacific Northwest National Laboratory (PNNL) for catalytic hydrotreating of bio-oils in a two-stage, fixed-bed, continuous-flow catalytic reactor. The configurations of the reactor systems, the operating procedures, and the processing and analysis of feedstocks, bio-oils, and biofuels are described in detail in this paper. We also demonstrate hot-vapor filtration during fast pyrolysis to remove fine char particles and inorganic contaminants from bio-oil. Representative results showed successful conversion of biomass feedstocks to fuel-range hydrocarbon biofuels and, specifically, the effect of hot-vapor filtration on bio-oil production and upgrading. The protocols provided in this report could help to generate rigorous and reliable data for biomass pyrolysis and bio-oil hydrotreating research.

**INTRODUCTION:**

Our society depends heavily on fossil fuels (e.g., oil, natural gas, coal, etc.). These resources are not sustainable energy sources and are being depleted at a rapidly increasing rate, leading to concerns regarding dwindling fossil-fuel resources, environmental consequences of CO<sub>2</sub> emission, and economic problems.<sup>1,2,3,4</sup> There is increasing demand for alternative and sustainable energy sources. Biomass is the only renewable and carbon-neutral resource for production of liquid fuels (biofuels) and carbon-based chemicals to replace fossil fuels in the current energy production and conversion system.<sup>3,4</sup>

Lignocellulosic biomass (e.g., woods, grass, energy crop, agricultural waste, etc.), which is currently the most abundant and least expensive biomass source, has attracted the most attention as a way to produce biofuels via various thermochemical and biological routes.<sup>3,4</sup> Three primary routes have been the focus of the recent research: 1) biochemical conversion to sugars followed by aqueous-phase catalytic and biochemical processing to biofuels; 2) gasification to synthesis gas followed by catalytic conversion to biofuels or alcohols; and 3) pyrolysis or liquefaction to liquid bio-oils followed by catalytic upgrading to biofuels.<sup>3,4</sup> The first route can only utilize the cellulose and hemicellulose portion of lignocellulosic biomass. Pyrolysis integrated with upgrading is considered to be a near-term viable technology for the direct production of biofuels. Pyrolysis is the thermal decomposition of lignocellulosic biomass at temperatures between 400 and 550 °C in the absence of oxygen.<sup>4,5,6</sup> A number of reactions, such as depolymerization, dehydration, and C–C bond cleavage, occur during pyrolysis and lead to the formation of a complex mixture of more than 200 oxygenated

compounds.<sup>4,5,6</sup> Bio-oils in high yields (up to 80 wt % of dry feed) could be produced with up to 70% of the energy stored in the biomass feedstocks retained.<sup>4,5</sup> However, direct use of the produced pyrolysis bio-oil as transportation fuels in standard equipment is problematic because of the high oxygen and water content, which lead to different physical and chemical properties such as high viscosity, corrosiveness, poor volatility, low heating value, and poor stability.<sup>6,7,8,9</sup> Therefore, extensive oxygen removal is required to upgrade bio-oils to fuel-range hydrocarbons. Catalytic hydrotreating using solid catalysts in hydrogen is the most common route to upgrade bio-oil by oxygen removal through hydrodeoxygenation and hydrogenation reactions.<sup>6,7,8,9</sup>

Currently, one of the primary challenges for pyrolysis followed by hydrotreating is to achieve long-term steady operation, especially for the hydrotreating process in which the thermal instability of the bio-oil and inorganic and sulfur residues in bio-oil could cause significant catalyst deactivation.<sup>10,11</sup> The thermal instability of bio-oil has been addressed by low-temperature hydrogenation to stabilize the active species in bio-oil.<sup>11,12</sup> Cleanup of bio-oil by removing inorganic residues, which could catalyze repolymerization of bio-oil fractions and deactivate hydrotreating catalysts by deposition, may be valuable. Hot-vapor filtration is one of the techniques to effectively reduce the inorganic content in bio-oil by removing char particulates during pyrolysis.<sup>13,14,15</sup> Hot-vapor filtration is used downstream of the pyrolysis reactor to separate char fines from the pyrolysis gas/vapor stream at high temperature before condensation of the vapors.<sup>13,14,15</sup>

We report here the protocol used at the National Renewable Energy Laboratory (NREL) for biomass fast pyrolysis both with and without hot-vapor filtration to produce bio-oils using a fluidized-bed reactor and at Pacific Northwest National Laboratory (PNNL) for bio-oil hydrotreating to produce biofuels in a continuous-flow packed-bed catalytic reactor. The configurations of the reactor systems, the operating procedures, and the processing and analysis of feedstocks, bio-oils, and biofuels are described in detail. Results of pyrolysis processing of a representative biomass feedstock with or without hot-vapor-filtering and hydrotreating of the produced bio-oil are also presented along with an assessment of the impact of hot-vapor filtration.

## **PROTOCOL:**

### **1. Fast pyrolysis with hot vapor filtration**

#### **1.1. Biomass feedstock preparation**

1.1.1. Mill the biomass to a particle size of <2 mm. Store in a cool, dry place.

#### **1.2. Assemble pyrolysis system**

##### **1.2.1. Assemble pyrolysis reactor.**

1.2.1.1. Mount reactor inside furnace. Connect fluidizing nitrogen, auger nitrogen, and air lines to reactor. Insert Auger into jacketed auger port. Connect cooling air to jacket.

1.2.1.2. Mount and connect auger motor.

1.2.1.3. Mount solid feeder 30 to 60 cm directly above the vertical opening of the auger port.

1.2.1.4. Mount lock hopper between the solid feeder outlet and the vertical opening of the auger port. Connect to the auger port with nylon-braid, reinforced vinyl tubing with an inner diameter of 25 mm. Secure the tubing to the auger port with a hose clamp. Connect to feeder with a light-weight, clear, loose plastic slip-fit.

### **1.2.2. Assemble cyclone and hot filter.**

1.2.2.1. Mount cyclone and connect cyclone inlet to reactor outlet. Close-couple receiver to cyclone.

1.2.2.2. Mount hot filter (made of stainless steel with a pore size of 2  $\mu\text{m}$ ) in the filter housing. Connect cyclone outlet to hot-filter inlet. Connect nitrogen purge and pressure relief to cyclone outlet.

1.2.2.3. Use heat tape and insulating blankets to heat the trace from the cyclone inlet to the condenser inlet.

### **1.2.3. Assemble condenser system.**

Note: Mount the pieces of the condenser system in a fume hood using laboratory-jacks, ring-stands, and laboratory clamps.

1.2.3.1. For the first condenser, couple 15 to 30 cm of 1.2-cm (outer diameter) stainless steel tubing to quartz tubing with a standard taper joint. Connect the first condenser to a 500-mL, two-necked (standard taper), round-bottomed flask (receiver) placed in a container that will serve as an ice bath. Make connections between vessels downstream of this point with 9- to 12-mm clear vinyl tubing secured with hose clamps on ground glass joints, spherical joints, and hose barbs on the glassware.

1.2.3.2. Connect the outlet of the first condenser flask to the lower side port (inlet) of the electrostatic precipitator (ESP).

1.2.3.3. Connect the upper side port (outlet) of the ESP to the small upper connection of the dry-ice trap (cold-finger condenser).

1.2.3.4. Connect a U-tube to line between the ESP and the dry-ice trap. Fill the U-tube half full with water.

1.2.3.5. Connect the dry-ice trap to a 500-mL, two-necked, round-bottomed flask (receiver) placed in a container that will serve as a dry-ice bath.

1.2.3.6. Connect the outlet of the 500-mL flask to the inlet (center port) of the housing of the coalescing filter.

1.2.3.7. Place a container for holding dry ice around the bottom of the filter housing.

1.2.3.8. Connect the filter outlet to the dry-test meter and other gas analysis instruments (here non-dispersive infra-red analyzers for CO, CO<sub>2</sub>, and CH<sub>4</sub>, detector for hydrogen, and micro-gas chromatography (micro-GC) for CO, CO<sub>2</sub>, nitrogen, hydrogen, and C1-C4 hydrocarbons) and then to vent.

Note: Schematic of the pyrolysis reactor system is shown in Figure 1. Pictures of the biomass feeder, pyrolyzer, cyclone, hot-vapor filter, and the condensers of the pyrolysis reactor system are shown in Figure S1 to S4 in the supplemental file.

### **1.3. Load pyrolysis reactor**

1.3.1. Pour 200 mL of sand (330 g) into the reactor.

1.3.2. Pour 2 kg of ground biomass into the feed hopper.

### **1.4. Leak check pyrolysis system**

1.4.1. Cap off system at the condenser inlet.

1.4.2. Pressurize to 0.05 MPa or expected maximum operating pressure, whichever is higher. Ensure that the flow required to maintain the pressure is <200 mL/min. If not, locate and fix leak, and repeat this step.

1.4.3. Relieve pressure, uncap system, connect condensation system, cap at exit end of condensation system.

1.4.4. Pressurize to 0.01 MPa. Ensure that a flow of <200 mL/min maintains the pressure. If not, locate and fix the leak, and repeat this step.

1.4.5. Depressurize and reconnect the condensation system to instruments.

### **1.5. Heat up reactor**

1.5.1. Turn on cooling air, set fluidizing nitrogen flow to 3 L/min and auger nitrogen flow to 1 L/min.

1.5.2. Set furnace target temperature to 500 °C and other heaters to 400 to 500 °C.

1.5.3. Ramp temperature up to target temperatures at a rate of 1 to 10 °C/min.

## **1.6. Prepare to operate**

1.6.1. Increase fluidizing nitrogen flow rate to 14 L/min, auger nitrogen flow rate to 1.4 L/min, and introduce purge gas at a flow rate of 0.5 L/min.

1.6.2. Fill bath under first condenser with ice. Fill dry-ice trap container under its receiver, and container around coalescing filter with dry ice.

1.6.3. Monitor temperature inside of coalescing filter with thermocouple placed on the surface of the filter and adjust dry-ice level so it is 0°C.

## **1.7. Perform pyrolysis experiment**

1.7.1. Turn on lock-hopper valves (use 4 second cycle) and auger.

1.7.2. Turn on ESP. Set voltage to 5 to 10 kV as needed to observe an arc at least once every 2 seconds.

1.7.3. Use micro-GC to verify that no oxygen is present. Verify that turning on the auger and lock hopper did not cause a decrease in output gas flow rate indicated by the dry test meter, which would indicate the presence of a leak.

1.7.4. Turn on feeder at 100 g/hr. Observe the bed temperature, and increase the set point as needed to compensate for increased heat load.

1.7.5. When temperature has recovered to within 2 °C of 500 °C, increase feed rate by 100 g/hr. Repeat this until a feed rate of 420 g/hr is reached.

1.7.6. Every 15 minutes, record bed temperature, feed rate on auger controller, gas concentrations by micro-GC, dry test meter rate, and system pressures by pressure gauges. Verify that ESP is still arcing correctly. Respond to changes in any of these as needed. Refill ice and dry ice. Drain the ESP into a product collection jar as needed.

## **1.8. Shutdown**

1.8.1. After feeding 1 kg of biomass, stop feeding.

1.8.2. After gas levels have decayed to less than 10% of steady-state values, turn off all heaters, turn down flows to fluidizing at 3 L/min and auger at 1 L/min. Turn off ESP and auger.



1.8.3. Allow system to cool (4 to 6 hours) before opening the hot sections.

### **1.9. Collect liquid products and char.**

1.9.1. Weigh all parts of the condenser system to obtain total liquid yield. Pour liquids from the condenser receivers into a common jar or bottle. Alternatively, use acetone to clean the glassware.

1.9.2. Empty char receiver into a jar. Remove hot filter, empty the housing, and brush off the filter into the char jar. Weigh the filter. Remove and weigh the bed material. Use a HEPA vacuum with a knock-out vessel for this service.

### **1.10. Oxidize the system.**

1.10.1. Seal the reactor, cyclone receiver, and cleaned hot filter. Check for leaks as described above in Section 1.4.

1.10.2. Install a metal line from the condenser inlet to the outlet of the coalescing filter to bypass the condensation system.

1.10.3. Heat the reactor to 550 °C with 3 L/min nitrogen as the fluidizing gas and 1 L/min auger nitrogen flow.

1.10.3. Add air to the fluidizing gas. Start at 0.2 L/min and gradually increase to 4 L/min. Continue until CO + CO<sub>2</sub> concentrations are less than 0.1%.

### **1.11. Calculate yields.**

1.11.1. Calculate liquid yield as the total change in mass of the condensation system.

1.11.2. Calculate char yield as the sum of the weight change in the bed, the weight change of the hot filter, and the char collected from the cyclone receiver and hot-filter housing.

Note: Additional char could be estimated from the oxidation of the system, but this is usually unimportant.

1.11.3. Calculate gas yield as the total weight of gaseous products from the gas concentrations measured on the GC and the flow rate of the dry test meter.

## **2. Catalytic hydrotreating of bio-oil**

Note: The bio-oil samples produced at NREL were shipped to PNNL for catalytic hydrotreating on a hydrotreater system.

## 2.1 Hydrotreater system

2.1.1. Ensure that the hydrotreater system is in operational condition by checking each component.

Note: The hydrotreater reactor system used is configured as a single-pass, co-current, continuous, down-flow catalytic reactor. The system consists of three major components: 1) a gas and liquid feeding component, 2) a heated reactor, and 3) a gas-liquid product separation component (Figure 2). The system is designed to operate at up to 13.6 MPa (2000 psig; maximum operating pressure) with a maximum catalyst temperature 500 °C (only the reactor is rated at this temperature).

2.1.2. Ensure that the hydrotreater monitoring and controlling system and the safety control system are in operational condition.

Note: The system is monitored and partially controlled by an in-house, built computer program with various sensors. Sensors include thermocouples and pressure transducers for the reactor as well as hydrogen and ventilation sensors in the enclosure where the reactor is located. Data are recorded by the program to monitor the reactor. The outlet gas flow rate is measured by a flow meter, and data are recorded by its accompanying software. The program also controls the power supply of major equipment of the reactor. During an experiment, if the reactor undergoes an unwanted change in operating conditions in terms of specific pressure changes and/or temperature changes, or a combustible gas is present above the safety limit, and/or if the ventilation system fails, the program could automatically shut down the system to ensure safety. Pressure relief valves and a rupture disc also are installed in the hydrotreater system to protect against over-pressurization.

## 2.2. Catalyst loading and pretreatment

### 2.2.1. Catalyst preparation

2.2.1.1. Crush both catalysts, Ru/C, as the stage-I catalyst and CoMo/Al<sub>2</sub>O<sub>3</sub> as the stage-II catalyst, and sieve to retain 0.25 to 0.60 mm (30 to 60 mesh) grains.

Note: Ru/C catalyst was prepared in-house and CoMo/Al<sub>2</sub>O<sub>3</sub> catalyst was a commercial product.

### 2.2.2. Catalyst loading into the reactor

2.2.2.1. Use stainless steel tubes and screens as the support media for the catalyst beds. Slowly pour the stage-II catalyst grains, the stage-I catalyst grains, and the original stage-I catalyst extrudates, which were used as distributor, into the reactor sequentially while "tapping" on the outside of the reactor to form packed catalyst beds. Load 32 mL of each catalyst to form a two-stage catalyst bed with 24 mL of each catalyst located in the isothermal zone (Figure 3).

### **2.2.3. Install the reactor to the hydrotreater system**

2.2.3.1. Place the reactor into the hydrotreater system by installing the two heaters and then connecting the reactor to the gas and liquid feed component and the gas-liquid separation component.

Note: Two heat tape-heated aluminum sheaths enclose the tubular reactor to provide heat. Each heated sheath is used independently to heat the portion of reactor during catalyst pretreatment and during hydrotreatment testing. Each aluminum sheath is wrapped with a high temperature heat tape and insulation and heated using a temperature controller. The tubular fixed-bed catalytic reactor is made of 316 stainless steel and with an inner diameter of 13 mm and a length of 64 cm. A thermocouple well (4.7 mm outside diameter) is located in the center of the reactor, and two thermocouples are placed in the well to measure the temperature of the catalyst beds.

2.2.4. Check the pressure of the hydrotreater system for leaks using 12.0 MPa helium gas by keeping the system at the pressure and ensuring that the drop of pressure is lower than 1 psig per hour.

### **2.2.5. Catalyst pretreatment. Sulfide the catalysts in situ in hydrogen and sulfiding agent flow.**

2.2.5.1. Heat both catalyst beds from room temperature to 150 °C in hydrogen at heated at a rate of 120 °C/h.

2.2.5.2. Maintain both catalyst-bed temperatures at 150 °C for 2 hours in hydrogen and sulfiding agent (35 wt% di-tert-butyl disulfide in decane fed by a feeding pump).

2.2.5.3. Heat the stage-I bed from 150 to 250 °C at a rate of 83.3 °C/h, and maintain at 250 °C for 5.8 hours in hydrogen and sulfiding agent flow. During the same period, heat the stage-II bed from 150 to 400 °C at a rate of 83.3 °C/h, and maintain at 400 °C for 4 hours in hydrogen and sulfiding agent.

2.2.5.4. Stop the sulfiding agent flow and maintain hydrogen flow. Then set the temperature of the each catalyst bed to the desired reaction temperature. During the procedure, keep the pressure of the reactor at 10.3 MPa, the sulfiding agent flow rate at 0.128 mL/min, and the hydrogen flow rate at 242 mL/min.

Note: The sulfiding agent flow rate is determined by the amount of catalyst used and the sulfiding agent liquid hourly space velocity (LHSV) of 0.12 mL/mL-cat/h for overall catalysts. The hydrogen flow rate is determined by the sulfiding agent flow rate and the hydrogen-to-sulfiding agent flow ratio at 1890 mL hydrogen/mL sulfiding agent liquid. The gas and liquid feeding components of the hydrotreater system consist of two high-pressure syringe pumps. One of the two pumps is used to feed the sulfiding agent. The gas and sulfiding agent is introduced to the

pre-reactor zone of the reactor where the liquid is mixed before they pass downward through the catalyst bed in the reactor.

### **2.3. Bio-oil hydrotreating**

2.3.1. Set the temperatures of the stage-I catalyst bed and the stage-II catalyst bed to 220 and 400°C, respectively. Adjust the hydrogen flow to 152 mL/min and maintain the system pressure at 10.3 MPa.

Note: The hydrogen flow rate is determined by the amount of catalyst used, the bio-oil LHSV of 0.20 mL/mL-cat/h for each stage, and the hydrogen-to-bio-oil ratio of 1900 mL hydrogen/mL bio-oil.

2.3.2. Record the bed temperature and hydrogen flow baselines when the temperature, pressure, and hydrogen flow become stable.

2.3.3. Add di-tert-butyl disulfide to bio-oil feed at an amount equal to 150 ppm sulfur in bio-oil. Fill the bio-oil feed in one of the feeding pumps and purge the feeding line until a liquid flow that is free of air bubbles is achieved.

2.3.4. Pressurize the pump to 10.3 MPa, and then connect to the reactor by opening the connecting valves. Start feeding the bio-oil at a flow rate of 4.8 mL/h. This action starts the bio-oil hydrotreating test.

Note: Bio-oil flowrate is determined by the amount of catalyst used and the bio-oil LHSV of 0.20 mL/mL-cat/h for each stage. The hydrogen gas and bio-oil are introduced to the pre-reactor zone of the reactor where the gas and liquid are mixed before they pass downward in an assumed trickle flow through the catalyst bed in the reactor.

2.3.3. Check the status of the reactor and record the parameters, such as temperature, pressure, flow rate, and volume, periodically. Ensure the catalyst-bed temperatures are within  $\pm 2^\circ$  of the desired temperature, the gas and liquid flow rates are exactly the same as the desired settings, and reactor pressure is within  $\pm 0.15$  MPa of the desired pressure. Ensure the pressure drop across the catalyst bed is  $<0.35$  MPa.

Note: The system is monitored and partially controlled by an in-house built computer program with various sensors. Sensors include thermocouples and pressure transducers for the reactor as well as hydrogen and ventilation sensors in the enclosure where the reactor is located.

2.3.4. Analyze outlet gas samples every 2 hours by directing the off-gas through an on-line micro-GC.

Note: The micro-GC is a four-channel micro-GC and calibrated using a calibration gas before each hydrotreating test.

2.3.5. Collect liquid samples every 6 hours using the following procedure: switch the sampling trap to the bypass trap, reduce the pressure of the sampling trap, drain the liquid sample to collecting vials, purge the sampling trap with helium, pressurize the sampling trap with helium, and redirect product flow to the sampling trap. Operate a series of two- and three-way valves that divert the gases and products in the desired directions.

Note: Once the reactants pass through the catalyst beds, the liquid products and unreacted liquids are separated from the gaseous products and unreacted gases in the gas-liquid separation system. The hot gases pass through one of two pressurized, chilled, liquid/gas cold traps (sample trap or bypass trap) placed in parallel downstream of the reactor system. The off-gas then passes through the back-pressure regulator where the pressure is reduced to atmospheric pressure. The off-gas is then passed through a gas meter to measure the flowrate.

2.3.6. Conduct the test for 60 hours on stream (time on stream [TOS]). Terminate the test by stopping the bio-oil feed. Set the reactor temperature to 100°C and hydrogen flow rate to 100 mL/min.

Note: The test could be operated for TOSs ranging from fifty to several hundred hours.

## **2.4. Post-test procedure**

2.4.1. Use acetone to clean the feeding pump for feeding bio-oil. Load the cleaned feeding pump with acetone.

2.4.2. Purge the catalyst bed with ~400 mL acetone at an acetone flow rate of 10 to 40 mL/min and a hydrogen flow rate of 100 mL/min when the catalyst-bed temperatures are at 100 °C.

2.4.3. Shut off the heaters of the reactor, depressurize the system to ambient pressure, and purge the reactor with helium for at least 24 hours.

2.4.4. Remove the reactor from the system and remove the spent catalysts from the reactor.

## **2.5. Product processing and result analysis**

2.5.1. For liquid product processing, separate the two phases and weigh individually. The liquid products are normally in two phases, a light oil phase (oil product) and a heavy aqueous phase (aqueous product).

2.5.2. Conduct the following analyses of the oil product: density measurement; Karl Fischer titration for water content; elemental analysis (D5291/D5373, D5373mod, and D1552/D4239) for carbon, hydrogen, nitrogen, oxygen, and sulfur; semi-micro color indicator titration (D3339) for total acid number; inductively coupled plasma-optical emission spectroscopy for inorganic content; and simulated distillation (ASTM D2887) to assess the relative amounts of fuel

products in the gasoline, diesel, jet fuel, and residual ranges. Conduct the following analyses of the aqueous products: Karl Fischer titration for water content and elemental analysis (D5291/D5373) for carbon, hydrogen, and nitrogen content<sup>15</sup>.

2.5.3. Calculate the yields of produced oil product, aqueous product, and gaseous product; the hydrogen consumption; and the mass balance based on the inlet reactant flow rate and density, inlet hydrogen flowrate, outlet oil product weight, water content of the outlet oil product, outlet aqueous product weight, outlet gas flow rate, and outlet gas composition.

2.5.4. Analyze spent catalysts by inductively coupled plasma-optical emission spectroscopy<sup>15</sup>.

### **REPRESENTATIVE RESULTS:**

The fast pyrolysis of a representative herbaceous biomass, switchgrass, with or without hot-vapor filtration and the catalytic hydrotreating of the product bio-oil are used as an example for the process reported here. More details of these experiments could be found in detail in our recent publication.<sup>15</sup>

#### **Hot-vapor-filtered fast pyrolysis**

Table 1 shows bio-oil, char, and gas yields produced with and without the hot-vapor filter for a typical herbaceous feedstock. For the control experiment without hot-vapor filtration, the vapors passed through the filter housing but the filter was not installed. This kept the residence time in the two experiments the same so any difference is due to the filter only. The bio-oil yields were 52 to 56%, indicating successful conversion of the major portion of the biomass to liquid intermediate oils. A photo of a reparative bio-oil sample is shown in Figure 4. The mass balance closures were 86 to 90%. Light vapors that were not properly collected in the condensation train were one source for mass losses. Pyrolysis oils contain several low-boiling-point compounds, such as hydroxyacetaldehyde (boiling point 20.2 °C), that are difficult to condense. Adding a second dry-ice trap will improve the recovery of the light condensable compounds. Performing experiments with higher biomass feed rates than reported here will improve recovery of the light vapors by increasing the vapor concentration prior to condensation. The escape of light condensable compounds can be verified by gas chromatography-mass spectroscopy analysis of the exit gas. The mass balances were relatively low for the herbaceous feedstock, likely because of escaping light char, which was produced from the switchgrass in relatively large quantities. Cracking reactions occur at the filter so inclusion of the hot-vapor filter reduced the oil yields and increased the gas yields.

Table 2 and Figure 5 shows the analysis results of herbaceous feedstock and the bio-oils produced. Hot-vapor filtering reduced the ash residue in the bio-oil from 1.45% to below the detection limit. Various inorganics, such as aluminum, calcium, iron, potassium, magnesium, sodium, phosphorous, and silicon, were observed in the bio-oils, and they mainly originate from the biomass feedstock. Hot-vapor filtering significantly decreased the inorganic contents in the bio-oil, indicating that hot-vapor filtering was a powerful protocol for effectively reducing the trace element content in the bio-oils by removing char and ash particulates. Hot-vapor filtering also decreased the carbon content and increased the oxygen content in the bio-oils. Woody

feedstocks have low ash contents compared to herbaceous feedstocks, and lower reductions in the bio-oil ash and inorganic contents are observed.<sup>15</sup>

### **Catalytic hydrotreating of bio-oil**

The analytical results of the produced bio-oil were consistent with the fact that bio-oils produced from such process are not of sufficient quality for direct use in internal combustion engines. Therefore, upgrading of bio-oil is required. The two bio-oil samples were upgraded by catalytic hydrotreating in the hydrotreater system under the conditions discussed above.

Bio-oils are known to plug the hydrotreating reactors as chars or polymerization products of active species in bio-oils accumulate in the catalyst bed. Therefore, the pressure drop across the catalyst beds during the hydrotreating tests is an important indicator of accumulating chars or polymerization products. The hot-vapor filtered bio-oil performed nearly flawlessly for 60 hours TOS in the hydrotreating test. However, the non-filtered bio-oil had ~5 wt% undissolved solids, which separated out in the pump and were not treated. Even with these untreated solids, there was still a pressure drop buildup after 50 hours TOS, probably because of the residual solids in the non-filtered bio-oil plugging the packed catalyst bed.

Tables 3 and 4 and Figure 5 list the yield of the products for bio-oil hydrotreating at different TOSs. Phase-separated liquid products, including an upgraded oil phase and an aqueous phase, and gaseous products, including CH<sub>4</sub>, C<sub>2</sub>H<sub>6</sub>, C<sub>3</sub>H<sub>8</sub>, C<sub>4</sub>H<sub>10</sub>, CO, and CO<sub>2</sub>, were produced. Figure 4 shows a photo of a reparative upgraded oil sample. Table 5 shows the analysis results of upgraded oil and Figure 5 compares the elemental analysis results of the bio-oil and the upgraded oil. Hydrotreating was very effective at reducing oxygen, sulfur, and nitrogen and adding hydrogen significantly from the bio-oil feed. The oxygen content in the upgraded oil was ~2.0 wt%, which was significantly lower than 35 to 40 wt% of oxygen in the bio-oil feed. The hydrogen-to-carbon ratio of the upgraded oil was ~1.7, compared to ~1.3 for the bio-oil feed. The trend of density of the upgraded oil, which increased from 0.81 to 0.83 g/mL over the period of the test, suggests a mild catalyst deactivation over the 60 hour TOS.

Comparisons of hydrotreated products between the hot-vapor filtered and non-filtered bio-oil showed that hot-vapor filtered bio-oil led to a slightly higher water-to-upgraded oil ratio, which is consistent with the higher oxygen content in the hot-vapor-filtered bio-oil feed. The properties of upgraded oil for the two bio-oils were very similar. The major difference between the hydrotreating of hot-vapor-filtered and non-filtered bio-oil was that the used catalyst beds of hot-vapor-filtered bio-oil showed much less deposition of inorganics compared to the catalyst beds used with non-filtered bio-oils.

**Figure 1. Schematic for the 5-cm fluidized-bed pyrolysis reactor system.** There is a hot-vapor filter, a condensation system, and a gas-measurement system.

**Figure 2. Schematic of the mini-reactor hydrotreater system.** (MFC: mass flow controller; RD: rupture disc; PT: pressure transducer; PI: pressure indicator (gauge); BPR: back-pressure regulator; PR: pressure regulator)

**Figure 3. Schematic of the catalyst bed in the mini-hydrotreater reactor.** The temperature profile of the catalyst bed is shown in the left and the position of catalysts of each stage is shown in the right.

**Figure 4. Photos of a representative bio-oil samples (left) and a representative upgraded oil sample (right).**

**Figure 5. Comparison of elemental analysis results of the herbaceous feedstock (switchgrass), the bio-oil produced with hot-vapor filtration, and the upgraded oil.** Carbon, hydrogen, and oxygen content did not change much after fast pyrolysis of biomass, however, oxygen content decreased significantly and hydrogen content increased after bio-oil hydrotreating.

**Table 1.** Yields of major pyrolysis products (bio-oil, char, and gas) and mass balance closures for pyrolysis of an herbaceous feedstock (switchgrass) with and without hot-vapor filtration

**Table 2.** Analysis of the representative herbaceous feedstock (switchgrass) and bio-oil produced with and without hot-vapor filtration

**Table 3.** Yield of major hydrotreating products at the different TOSs for hot-vapor filtered and non-filtered representative bio-oil

**Table 4.** Produced gas composition during the hydrotreating of representative bio-oils

**Table 5.** Analysis of the upgraded oil products from the hydrotreating of representative bio-oils

## **DISCUSSION:**

In this paper, we described a detailed procedure for converting lignocellulosic biomass to fuel-range hydrocarbons via fast pyrolysis and catalytic hydrotreating. The NREL pyrolysis reactor system with a 5.0-cm inner diameter fluidized-bed reactor and the PNNL hydrotreater system with a 1.3-cm inner diameter fixed-bed catalytic reactor and their operation procedures are described in detail. These reactor systems could be used to conduct pyrolysis and hydrotreating tests in an efficient and safe manner. We used representative herbaceous feedstocks to produce liquid bio-oils in the pyrolysis reactor system, and then, the bio-oils were processed in the hydrotreating system with a two-stage catalyst bed including sulfided Ru/C and CoMo/Al<sub>2</sub>O<sub>3</sub> as catalysts to produce fuel-range liquid hydrocarbons. The process also is applicable to pyrolysis of a wide range of biomass feedstocks including wood, grass, and cornstover and then upgrading the produced bio-oil to produce biofuels.<sup>16</sup> The hydrotreater and hydrotreating process also could be used for upgrading other biomass-generated intermediates such as liquefaction oil (bio-crude) from biomass such as wood and algae.

Maximizing bio-oil yield during pyrolysis requires heating the biomass rapidly to sufficient temperature to achieve maximum volatilization of the biomass. For most biomass, this means temperatures of 500 to 600 °C. A fluidized bed provides rapid heat transfer from the sand to



the biomass, providing a high heating rate. The use of small particles also provides a higher heating rate. Typically a few percent higher bio-oil yield is achieved with biomass ground to <0.5 mm than with biomass ground to <2 mm. Maximizing yield also means minimizing thermal cracking of the vapors by keeping the residence time at temperature low (1 to 2 seconds). Pyrolysis vapors contain compounds with a wide range of boiling points. Thus, the hot piping tends to become fouled with liquid, repolymerized vapors and char. To avoid this condition, keep the auger temperature below 100 °C and all surfaces between the reactor and condensation train above 400 °C to avoid fouling, but below 500 °C to minimize thermal cracking. Thorough coverage with heat tape is necessary to prevent cold spots and provide a uniform temperature. Sewn insulation pads with closures on them generally provide more uniform coverage, thereby resulting in more uniform temperature. It is important that the temperature drops rapidly in the first condenser to minimize the opportunity for repolymerization of high-boiling-point materials, which could lead to blockage of the condenser inlet. It also is necessary to use dry ice in the second condenser to maximize liquid recovery and prevent damage to gas-measurement and analysis instruments.

Some enhanced features were not mentioned in the basic fast pyrolysis procedure. It is useful to have a pressure gauge or transmitter near the reactor inlet. In addition, it is useful to maintain differential pressure across the reactor and measure the final pressure and temperature at the dry test meter (to enable accurate volume calculations). It also is helpful to have additional thermocouples in the pyrolysis bed to verify that the bed is fluidizing uniformly enough to provide uniform temperatures. Typically, <5 °C spread is seen vertically through the bed. It also is useful to have nested-loop temperature control on the reactor. When a larger amount of oil is needed, it is helpful to install a valve on the bottom of the char receiver and mount a secondary char receiver below that, which in turn has a valve at the bottom with a jar loosely mounted to it. This makes it possible to empty the char receiver into the secondary receiver and finally down into the jar so that continuous operation can be maintained for many hours. Vibration is helpful to the operation. Manual pounding of the pipes can be used, but an automatic vibrator provides more reliable agitation. These can be operated continuously on the lock hopper and auger port to maintain a smooth feed flow through the feeder. Also, using an automatic vibrator on the secondary char receiver during char draining makes that operation much more reliable. Hot-vapor filtration enhances cracking and reduces bio-oil yield as shown above. Keeping the temperature of the filter low but still above condensation temperature (>400°C) minimizes cracking. An inert surface on the filter also may reduce cracking. The filter area needs to be large to reduce pressure drop.

The major limitation of the fast pyrolysis process is that the produced bio-oil has some major problematic properties such as high viscosity, corrosiveness, poor volatility, low heating value, and chemical instability, which limits their direct utilization and causes some issues during their upgrading.<sup>6,7,8,9</sup> Other variation of fast pyrolysis, catalytic fast pyrolysis, wherein fast pyrolysis is integrated with a catalysis process to upgrade the pyrolysis vapor, and hydrolysis, wherein fast pyrolysis conducted in the presence of reactive gases such as H<sub>2</sub>, can lead to a higher quality bio-oil but suffer higher operational complexity and low product yield.<sup>4,8</sup>

Two-stage catalytic hydrotreating showed good processing results for converting bio-oil to fuel-range hydrocarbons. Bio-oils are known to be chemically unstable because of the presence of active species such as carbonyl and phenolic compounds that could undergo repolymerization and condensation at a low temperature, leading to a high propensity for forming carbonaceous materials and consequent catalyst deactivation and even plugging of catalyst bed. Therefore, the first stage hydrogenation step was critical for the process, and was used to stabilize bio-oil by hydrogenation of carbonyls and phenolics at a relative low temperature by using a proper hydrogenation catalyst. The performance of the hydrogenation catalyst was the key of the long-term stability and operability of the process. Oxygen removal by hydrodeoxygenation occurred at the second stage by a sulfide-based hydrotreating catalyst. The yield and properties of produced final oil product depended on the catalysts and conditions used in the second stage. Maximizing the yield of liquid final fuels could be achieved by using catalysts capable of generating C-C bonds, such as alkylation function, and optimized reaction parameters including reaction temperature, pressure, and space velocity. The major limitation of the hydrotreating process is that, because of some problematic properties in bio-oil such as chemical instability and the presence of contaminants<sup>17</sup>, the lifetime of hydrotreating catalysts, especially the first step hydrogenation catalysts, are still limited, which makes the overall process costly. Maximizing the lifetime of the catalysts used could be achieved by using more robust catalysts; optimized reaction parameters including reaction temperature, pressure, and space velocity; or pretreatment to lower the content of the active species or contaminants in bio-oil feeds.

The hydrotreater was operated at high pressures and reactor temperatures with flammable gases and liquids involved. Therefore, safety rules and procedure should be strictly followed.

#### **ACKNOWLEDGMENTS:**

This work was supported by the U.S. Department of Energy (DOE) under Contract DE-AC36-08-GO28308 at NREL and Contract DE-AC05-76RL01830 at PNNL. The authors gratefully acknowledge the support of the DOE's Bioenergy Technologies Office.

#### **DISCLOSURES:**

The authors declare that they have no competing financial interests.

#### **REFERENCES:**

1. BP Statistical Review of World Energy, BP, <http://www.bp.com/content/dam/bp/pdf/Energy-economics/statistical-review-2014/BP-statistical-review-of-world-energy-2014-full-report.pdf> (2014).
2. International Energy Outlook 2014, U.S. Energy Information Administration, <http://www.eia.gov/forecasts/ieo/pdf/0484%282014%29.pdf> (2014).
3. Replacing the Whole Barrel, Bioenergy Technologies Office, EERE, DOE, 2013, [http://www1.eere.energy.gov/bioenergy/pdfs/replacing\\_barrel\\_overview.pdf](http://www1.eere.energy.gov/bioenergy/pdfs/replacing_barrel_overview.pdf).
4. Huber, G. W., Iborra, S., Corma, A. Synthesis of transportation fuels from biomass: Chemistry, catalysts, and engineering. *Chem. Rev.* **106** (9), 4044-4098, doi:10.1021/cr068360d (2006).

5. Mohan, D., Pittman, C.U.J., Steele, P. H. Pyrolysis of wood/biomass for bio-oil: A critical review. *Energy Fuels* **20** (3), 848-889, doi: 10.1021/ef0502397 (2006).
6. Bridgewater A. V. Review of fast pyrolysis of biomass and product upgrading. *Biomass Bioenergy* **29**, 68-94, doi:10.1016/j.biombioe.2011.01.048 (2012).
7. Elliott, D. C. Historical developments in hydroprocessing bio-oils. *Energy Fuels* **21** (3), 1792-1815, doi:10.1021/ef070044u (2007).
8. Wang, H., Male, J., Wang, Y. Recent advances in hydrotreating of pyrolysis bio-oil and its oxygen-containing model compounds. *ACS Catal.* **3** (5), 1047-1070, doi: 10.1021/cs400069z (2013).
9. Zacher, A. H., Olarte, M. V., Santosa D. M., Elliott D. C., Jones S. B. A review and perspective of recent bio-oil hydrotreating research. *Green Chem.* **16**, 491-515, doi: 10.1039/c3gc41382a (2014).
10. Elliott, D. C., *et al.* Catalytic Hydroprocessing of Fast pyrolysis bio-oil from pine sawdust. *Energy Fuels* **26** (6), 3891-3896, doi: 10.1021/ef3004587 (2012).
11. Venderbosch, R. H., Ardiyanti, A. R., Wildschut, J., Oasmaa, A., Heeresb, H. J. J. Stabilization of biomass-derived pyrolysis oils. *Chem. Technol. Biotechnol.* **85** (5), 674-686, doi: 10.1002/jctb.2354 (2010).
12. Olarte, M. V., *et al.* Towards long-term fast pyrolysis oil catalytic upgrading. *Prepr. Pap. Am. Chem. Soc., Div. Fuel Chem.* **58** (2), 230 – 231 (2013).
13. Scahill, J., Diebold, J. P., Feik, C. Removal of residual char fines from pyrolysis vapors by hot gas filtration. In *Developments in Thermochemical Biomass Conversion*; Bridgewater, A. V., Boocock, D. G. B., Eds.; Blackie Academic and Professional: London, U.K., 253-266 (1996).
14. Hoekstra, E., Hogendoorn, K. J. A., Wang, X., Westerhof, R. J. M., Kersten, S. R. A., van Swaaij, W. P. M. Fast pyrolysis of biomass in a fluidized bed reactor: In situ filtering of the vapors, *Ind. Eng. Chem. Res.* **48** (10), 4744-4756, doi: 10.1021/ie8017274 (2009).
15. Elliott, D. C., Wang, H., French R., Deutch S., lisa K. Hydrocarbon liquid production from biomass via hot-vapor-filtered fast pyrolysis and catalytic hydroprocessing of the bio-oil. *Energy Fuels* **28** (9), 5909-5917, doi: 10.1021/ef 501536j (2014).
16. Howe, D. et al. Field-to-Fuel Performance Testing of Lignocellulosic Feedstocks: An Integrated Study of the Fast Pyrolysis/Hydrotreating Pathway. *Energy Fuels.* **29** (5), 3188-3197, doi: 10.1021/acs.energyfuels.5b00304 (2015).
17. Wang, H., Wang, Y. Characterization of Deactivated Bio-oil Hydrotreating Catalysts. *Topics in Catalysis*. Published online, doi: 10.1007/s11244-015-0506-6 (2015).

Figure 1

[Click here to download Figure 1.tif](#)






Figure 2

[Click here to download Figure Figure 2.tif](#)










Figure 5


















**Table 1.** Yields of major pyrolysis products (bio-oil, char, gas) and mass balance closures for py

	Oil (wt.%)	Oil carbon yield (wt.%)	Char (wt.%)	Over-all
Hot-filtered	52.3	46.1	16.6	16.8
Non-filtered	56.3	56.4	19.3	14.5

pyrolysis of an herbaceous feedstock (switchgrass) with and without hot-vapor filtration.

Gas (wt.%)					Mass balance (wt.%)
H <sub>2</sub>	CH <sub>4</sub>	CO	CO <sub>2</sub>	C <sub>2</sub> H <sub>4</sub>	
0.06	0.9	5.3	10.2	0.43	85.7
0.03	0.7	4.3	9	0.38	90.1

**Table 2.** Analysis of the representative herbaceous feedstock (switchgrass) and pyrolysis oil

	Biomass feedstock	Bio-oil, hot-filtered
Moisture (wt.%)	6.1	29.5
C (dry basis, wt.%)	46	53.9
H (dry basis, wt.%)	6	6.09
O (dry basis, wt.%)	38.3	39.1
H/C ratio (dry basis)	-	1.34
N (dry basis, wt.%)	0.96	0.81
S (dry basis, wt.%)	0.16	0.1
Density (g/ml) at 40 °C	-	1.164
TAN (mg of KOH /g)	-	102
Viscosity (mm <sup>2</sup> /s) at 40 °C	-	19
Ash (wt.%)	8.06	<0.05
Trace analysis by ICP-OES (ppm, wt/wt)	Al	354
	Ca	6242
	Fe	330
	K	5966
	Mg	1818
	Na	193
	P	884
	Si	NA

Note: TAN means total acid number. ICP-OES means inductively coupled plasma-optical emission spectroscopy.

olysis oil products.

Bio-oil, non-filtered
24
55.9
6.21
34.8
1.32
1.08
0.1
1.158
98
9
1.45
12.8
330
11.1
535
141
40.2
68.9
182

mission spectroscopy.



**Table 3.** Yield of major hydrotreating products at the different TOS for Hot-Vapor-f

Bio-oil	TOS (h)	Upgraded oil yield	
		Wet basis (g/g)	Dry basis (g dry/g dry feed)
Hot-filtered	24-30	0.31	0.44
	36-42	0.33	0.47
	48-54	0.35	0.50
Non-filtered	48-54	0.27	0.44

Note: TOS means time on stream.

filtered and non-filtered representative bio-oil.

Gas yield (dry basis, g/g dry feed)	Produced water yield (dry basis, g/g dry feed)	H <sub>2</sub> consumed (dry basis, g H <sub>2</sub> /g dry feed)	Mass balance (%)
0.18	0.37	0.047	96
0.18	0.38	0.046	99
0.19	0.44	0.047	105
0.19	0.33	0.051	94

**Table 4.** Produced gas composition during the hydrotreating of representative bio-oils

Bio-oil	TOS (h)	CH <sub>4</sub>	C <sub>2</sub> H <sub>6</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>4</sub> H <sub>10</sub>	C <sub>5</sub> H <sub>12</sub>	CO	CO <sub>2</sub>
Hot-filtered	24-30	15.24	32.63	24.23	8.75	3.85	1.75	13.54
	36-42	14.7	30.68	23.33	8.49	3.7	2.25	16.85
	48-54	13.7	29.51	22.91	8.28	3.56	2.45	19.59
Non-filtered	48-54	12.44	25.77	23.69	5.68	3.89	3.07	25.45

Note: TOS means time on stream.

**Table 5.** Analysis of the upgraded oil products from the hydrotreating of representative bio-oils

Bio-oil	TOS (h)	C (wt.% dry basis)	H (wt.% dry basis)	H/C ratio	O (wt.% dry basis)	N (wt.% dry basis)
Hot-filtered	24-30	85.5	12.5	1.7	2	<0.05
	36-42	85.8	12.2	1.7	2	<0.05
	48-54	85.7	12.2	1.7	2.1	0.06
Non-filtered	48-54	85.6	12.3	1.7	2	0.06

Note: TOS means time on stream. TAN means total acid number.

S (wt.% dry basis)	Moisture (wt.%)	Density (g/ml)	TAN (mg KOH/g)
<0.02	<0.01	0.81	<0.01
<0.02	<0.01	0.82	<0.01
<0.02	<0.01	0.83	<0.01
<0.01	<0.01	0.83	<0.01

	Name of Material/ Equipment	Company	Catalog Number	Comments/Description
Pyrolysis system	Feedstock			Mill to pass 2 mm screen
	Sand for bed material	Black Rock		Screen to 300-500 microns
	Furnace	Thermcraft	J13667/1A	Split tube furnace 3.75 ID X 24 L
	Pyrolysis reactor	Custom-built at NREL		2" diameter, height 17", dual staggered plate distributor, 316SS, Auger port is 2.5 cm above distributor and is cooled with air or water, there is a coiled 1/4" 304 SS tube below the distributor to pre-heat the gas
	Cyclone	Custom-built at NREL		1" diameter
	Cyclone receiver	Custom-built at NREL		1 L capacity
	Cyclone secondary receiver	Custom-built at NREL		1 L capacity
	Hot vapor filter	Serv-A-Pure	SC2-0P10B34-X	316SS, 10 inches long, 2.0 MICRON
	2-neck round-bottomed flasks			500 mL
	Electrostatic precipitator	electrodes	Custom built	2" diameter 10" long ground electrode, glass enclosed, stop-cock on bottom
	High-voltage power supply	Spellman High Voltage	Bertan 803C-300P	30 kV max, 0.5mA
	Cold-finger condenser	Aldrich	Z164038	
	Coalescing filter	Finite	10C15-060	
	Dry test meter	American Meter	DTM-200A	with IMAC counter
	Gas chromatograph	Varian	CP-4900	M5SA, PBQ, CP-Sil columns
	Hydrogen detector	Gerhard Wagner	TCM-4	thermal conductivity detector
	Non-Dispersive Infrared Spectrometer	California Analytical	Model 300	Carbon monoxide 0-5%, 0-25%, carbon dioxide 0-5%, 0-20%, methane 0-5000 ppmv, 0-3%
	Mass flow controller	Celerity (now Tylan)	Unit 7301	0-20 SLM reactor bottom, 0-10 SLM auger, 0-2 slm purges, 0-5 slm air
	Auger	Auger Manufacturing Specialists	110520	3/8" Dia SS RH Auger 18"
	Motor for Auger	Leeson		Gearmotor-Parallel Shaft, 94RPM, 1/15 HP, TEFC, 115VAC
	Feeding system: Motor for hopper	Lenze	VDE0530	7KB4-7-100H Motor Ac Helical Gearbox 3PH 0.25 kW 1.4/0.82A
	Feeding system: Hopper and Loss in weight feeder	K-TRON Soder	KCL24T20	with K10S controller
	Feeding system: Valves	Swagelok	SS-65TS16	151 bar at 37°C and 6.8 bar at 232°C
	Control system	Opto22	SNAP-PAC parts	
	Heat cables	McMaster-Carr	4550T152 and similar	Extreme-Temperature (1400°F), heavy insulation for use on metal
	Ball Vibrator	Vibtec	K 8	
	U-tube	Custom-built at NREL		1/4" PFA and stainless steel tubing, 1.4 m tall
Hydrotreating system	Ru on carbon catalyst	Fabricated at PNNL		7.6 wt% Ru on carbon
	3% Co and 9% Mo on Al2O3 catalyst	Alfa-Aesar	45579	Cobalt oxide, typically 3.4-4.5%, Molybdenum oxide typically 11.5-14.5% on alumina
	Feeding pumps	ISCO	500D	Syringe pump, 500 ml cylinder capacity
	Mass flow controller	Brooks	SLA5850S1BAF4B1A1	
	Temperature controller	Cole-Parmer	WU-89000-10	Digi-Sense Advanced Temperature Controller, 115V
	Thermocouples	Omega		K-type thermocouples
	Pressure transducer	Omega	PX309-3KG5V	
	Heat tapes	Cole-Parmer	EW-03106-27	Dual element heating tape, 1/2in x 12ft, 936 watts, 120VAC w/ 2-prong plug
	Digital pressure gauge	Omega	DPG4000-3K	High Accuracy Digital Pressure Gauge, with Data Logging Capability
	Back pressure regulator	Mity-Mite		
	Gas flow meter	Mesa Labs	200-220L	Dry Cal, Definer 220 Low Flow
	Hydrotreating reactor, cross, tee, fittings	Parker, Autoclave		
	Combustible gas sensor	SMC	5100-02-IT-S1-01-00-0-0	COMBUSTIBLE GAS DETECTION SENSOR, 24 VDC POWER, ANALOG 4-20 MADC OUTPUT WITH MODBUS, NO RELAYS
	H2S sensor	SMC	5100-05-IT-S1-01-00-0-0	H2S TOXIC GAS SENSOR MODULE, 24VDC POWER, ANALOG 4-20 MADC OUTPUT WITH MODBUS, NO RELAYS
	Ventilation sensor	TSI	FHM10	Fume Hood Monitor FHM10
	Micro-Gas chromatograph	Inficon	Inficon 3000	Four-channel micro-GC with molecular sieve, Plot U, Alumina, and Stabilwax columns
	Lab-view based monitoring and controlling system	Custom-built at PNNL		Using National Instruments parts and Labview software



1 Alewife Center #200  
Cambridge, MA 02140  
tel. 617.945.9051  
www.jove.com

# ARTICLE AND VIDEO LICENSE AGREEMENT

Manuscript #:

Title of Article:

Author(s):

Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating

H Wang\*, DC Elliott\*, R French, S Deutch, and K Lisa.

Item 1 (check one box): The Author elects to have the Materials be made available (as described at <http://www.jove.com/publish>) via: ☐ Standard Access ☒ Open Access

Item 2 (check one box):

- ☒ The Author is NOT a United States government employee.
- ☐ The Author is a United States government employee and the Materials were prepared in the course of his or her duties as a United States government employee.
- ☐ The Author is a United States government employee but the Materials were NOT prepared in the course of his or her duties as a United States government employee.

## ARTICLE AND VIDEO LICENSE AGREEMENT

1. **Defined Terms.** As used in this Article and Video License Agreement, the following terms shall have the following meanings: "**Agreement**" means this Article and Video License Agreement; "**Article**" means the article specified on the last page of this Agreement, including any associated materials such as texts, figures, tables, artwork, abstracts, or summaries contained therein; "**Author**" means the author who is a signatory to this Agreement; "**Collective Work**" means a work, such as a periodical issue, anthology or encyclopedia, in which the Materials in their entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole; "**CRC License**" means the Creative Commons Attribution-Non Commercial-No Derivs 3.0 Unported Agreement, the terms and conditions of which can be found at: <http://creativecommons.org/licenses/by-nc-nd/3.0/legalcode>; "**Derivative Work**" means a work based upon the Materials or upon the Materials and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation, or any other form in which the Materials may be recast, transformed, or adapted; "**Institution**" means the institution, listed on the last page of this Agreement, by which the Author was employed at the time of the creation of the Materials; "**JoVE**" means MyJoVE Corporation, a Massachusetts corporation and the publisher of *The Journal of Visualized Experiments*; "**Materials**" means the Article and / or the Video; "**Parties**" means the Author and JoVE; "**Video**" means any video(s) made by the Author, alone or in conjunction with any other parties, or by JoVE or its affiliates or agents, individually or in collaboration with the Author or any other parties,

incorporating all or any portion of the Article, and in which the Author may or may not appear.

2. **Background.** The Author, who is the author of the Article, in order to ensure the dissemination and protection of the Article, desires to have the JoVE publish the Article and create and transmit videos based on the Article. In furtherance of such goals, the Parties desire to memorialize in this Agreement the respective rights of each Party in and to the Article and the Video.

3. **Grant of Rights in Article.** In consideration of JoVE agreeing to publish the Article, the Author hereby grants to JoVE, subject to **Sections 4 and 7** below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Article in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Article into other languages, create adaptations, summaries or extracts of the Article or other Derivative Works (including, without limitation, the Video) or Collective Works based on all or any portion of the Article and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. If the "Open Access" box has been checked in **Item 1** above, JoVE and the

## ARTICLE AND VIDEO LICENSE AGREEMENT

Author hereby grant to the public all such rights in the Article as provided in, but subject to all limitations and requirements set forth in, the CRC License.

4. Retention of Rights in Article. Notwithstanding the exclusive license granted to JoVE in **Section 3** above, the Author shall, with respect to the Article, retain the non-exclusive right to use all or part of the Article for the non-commercial purpose of giving lectures, presentations or teaching classes, and to post a copy of the Article on the Institution's website or the Author's personal website, in each case provided that a link to the Article on the JoVE website is provided and notice of JoVE's copyright in the Article is included. All non-copyright intellectual property rights in and to the Article, such as patent rights, shall remain with the Author.

5. Grant of Rights in Video – Standard Access. This **Section 5** applies if the "Standard Access" box has been checked in **Item 1** above or if no box has been checked in **Item 1** above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby acknowledges and agrees that, Subject to **Section 7** below, JoVE is and shall be the sole and exclusive owner of all rights of any nature, including, without limitation, all copyrights, in and to the Video. To the extent that, by law, the Author is deemed, now or at any time in the future, to have any rights of any nature in or to the Video, the Author hereby disclaims all such rights and transfers all such rights to JoVE.

6. Grant of Rights in Video – Open Access. This **Section 6** applies only if the "Open Access" box has been checked in **Item 1** above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby grants to JoVE, subject to **Section 7** below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Video in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Video into other languages, create adaptations, summaries or extracts of the Video or other Derivative Works or Collective Works based on all or any portion of the Video and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. For any Video to which this Section 6 is applicable, JoVE and the Author hereby grant to the public all such rights in the Video as provided in, but subject to all limitations and requirements set forth in, the CRC License.

7. Government Employees. If the Author is a United States government employee and the Article was prepared in the course of his or her duties as a United States government

employee, as indicated in **Item 2** above, and any of the licenses or grants granted by the Author hereunder exceed the scope of the 17 U.S.C. 403, then the rights granted hereunder shall be limited to the maximum rights permitted under such statute. In such case, all provisions contained herein that are not in conflict with such statute shall remain in full force and effect, and all provisions contained herein that do so conflict shall be deemed to be amended so as to provide to JoVE the maximum rights permissible within such statute.

8. Likeness, Privacy, Personality. The Author hereby grants JoVE the right to use the Author's name, voice, likeness, picture, photograph, image, biography and performance in any way, commercial or otherwise, in connection with the Materials and the sale, promotion and distribution thereof. The Author hereby waives any and all rights he or she may have, relating to his or her appearance in the Video or otherwise relating to the Materials, under all applicable privacy, likeness, personality or similar laws.

9. Author Warranties. The Author represents and warrants that the Article is original, that it has not been published, that the copyright interest is owned by the Author (or, if more than one author is listed at the beginning of this Agreement, by such authors collectively) and has not been assigned, licensed, or otherwise transferred to any other party. The Author represents and warrants that the author(s) listed at the top of this Agreement are the only authors of the Materials. If more than one author is listed at the top of this Agreement and if any such author has not entered into a separate Article and Video License Agreement with JoVE relating to the Materials, the Author represents and warrants that the Author has been authorized by each of the other such authors to execute this Agreement on his or her behalf and to bind him or her with respect to the terms of this Agreement as if each of them had been a party hereto as an Author. The Author warrants that the use, reproduction, distribution, public or private performance or display, and/or modification of all or any portion of the Materials does not and will not violate, infringe and/or misappropriate the patent, trademark, intellectual property or other rights of any third party. The Author represents and warrants that it has and will continue to comply with all government, institutional and other regulations, including, without limitation all institutional, laboratory, hospital, ethical, human and animal treatment, privacy, and all other rules, regulations, laws, procedures or guidelines, applicable to the Materials, and that all research involving human and animal subjects has been approved by the Author's relevant institutional review board.

10. JoVE Discretion. If the Author requests the assistance of JoVE in producing the Video in the Author's facility, the Author shall ensure that the presence of JoVE employees, agents or independent contractors is in accordance with the relevant regulations of the Author's institution. If more than one author is listed at the beginning of this Agreement, JoVE may, in its sole discretion, elect not take any action with respect to the Article until such time as it has received complete, executed Article and Video License Agreements from each



## ARTICLE AND VIDEO LICENSE AGREEMENT

such author. JoVE reserves the right, in its absolute and sole discretion and without giving any reason therefore, to accept or decline any work submitted to JoVE. JoVE and its employees, agents and independent contractors shall have full, unfettered access to the facilities of the Author or of the Author's institution as necessary to make the Video, whether actually published or not. JoVE has sole discretion as to the method of making and publishing the Materials, including, without limitation, to all decisions regarding editing, lighting, filming, timing of publication, if any, length, quality, content and the like.

11. Indemnification. The Author agrees to indemnify JoVE and/or its successors and assigns from and against any and all claims, costs, and expenses, including attorney's fees, arising out of any breach of any warranty or other representations contained herein. The Author further agrees to indemnify and hold harmless JoVE from and against any and all claims, costs, and expenses, including attorney's fees, resulting from the breach by the Author of any representation or warranty contained herein or from allegations or instances of violation of intellectual property rights, damage to the Author's or the Author's institution's facilities, fraud, libel, defamation, research, equipment, experiments, property damage, personal injury, violations of institutional, laboratory, hospital, ethical, human and animal treatment, privacy or other rules, regulations, laws, procedures or guidelines, liabilities and other losses or damages related in any way to the submission of work to JoVE, making of videos by JoVE, or publication in JoVE or elsewhere by JoVE. The Author shall be responsible for, and shall hold JoVE harmless from, damages caused by lack of sterilization, lack of cleanliness or by contamination due to the making of a video by JoVE its employees, agents or independent contractors. All sterilization, cleanliness or

decontamination procedures shall be solely the responsibility of the Author and shall be undertaken at the Author's expense. All indemnifications provided herein shall include ~~JoVE's attorney's fees and costs related to said losses or damages. Such indemnification and holding harmless shall include such losses or damages incurred by, or in connection with, acts or omissions of JoVE, its employees, agents or independent contractors.~~ T20

12. Fees. To cover the cost incurred for publication, JoVE must receive payment before production and publication the Materials. Payment is due in 21 days of invoice. Should the Materials not be published due to an editorial or production decision, these funds will be returned to the Author. Withdrawal by the Author of any submitted Materials after final peer review approval will result in a US\$1,200 fee to cover pre-production expenses incurred by JoVE. If payment is not received by the completion of filming, production and publication of the Materials will be suspended until payment is received.

13. Transfer, Governing Law. This Agreement may be assigned by JoVE and shall inure to the benefits of any of JoVE's successors and assignees. This Agreement shall be governed and construed by the internal laws of the Commonwealth of ~~Massachusetts~~ Washington State without giving effect to any conflict of law provision thereunder. This Agreement may be executed in counterparts, each of which shall be deemed an original, but all of which together shall be deemed to me one and the same agreement. A signed copy of this Agreement delivered by facsimile, e-mail or other means of electronic transmission shall be deemed to have the same legal effect as delivery of an original signed copy of this Agreement.

A signed copy of this document must be sent with all new submissions. Only one Agreement required per submission.


**CORRESPONDING AUTHOR:** Accepted in accordance with the attached Transfer of Copyright Agreement

Name: Tomiann Parker Authorized Agent signing for Battelle Memorial Institute authors only\*

Department:

Institution: Battelle Memorial Institute

Article Title:

Signature:  Date: 3/5/2015

Please submit a signed and dated copy of this license by one of the following three methods:

- 1) Upload a scanned copy of the document as a pdf on the JoVE submission site;
- 2) Fax the document to +1.866.381.2236;
- 3) Mail the document to JoVE / Attn: JoVE Editorial / 1 Alewife Center #200 / Cambridge, MA 02139

For questions, please email [submissions@jove.com](mailto:submissions@jove.com) or call +1.617.945.9051

**TRANSFER OF COPYRIGHT AGREEMENT**

The Copyright interest of Battelle Memorial Institute

Title: Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating

Authors: H Wang and DC Elliott

is hereby transferred to Jove

referred to hereinafter as the publisher, effective if and when the work is accepted for publication in  
Journal of Visualized Experiments

(A) If the work was authored under a contract with the U.S. Government, a nonexclusive, royalty-free license is retained by the Government to publish or reproduce the published form of the work, or allow others to do so, for U.S. Government purposes. This transfer is subject to the provisions of 48 CFR 970.5227-2.


(B) To the best of Battelle's and of the author's knowledge, the work contains no material whose publication would violate any copyright or other personal or proprietary right of any person or entity. The author(s) also guarantees that the work has not been published previously elsewhere by the author(s). No other warranty is expressed or implied by Battelle by this Transfer of Copyright or by executing any Publisher's agreement for the above identified work.

(C) The following rights are reserved by Battelle:

- (1) All proprietary rights other than copyright, such as patent rights.
- (2) The right to use all or part of the work in derivative works, such as lectures, lecture notes, reviews, textbooks, press releases, reprint books, booklets, or brochures prepared by or on behalf of Battelle Memorial Institute. The source and the publisher's copyright will be acknowledged.
- (3) The right to reproduce and make limited distribution of all or portions of the work for internal use. The source and the publisher's copyright will be acknowledged, and copies will not be offered for sale nor used so as to imply endorsement by the publisher of a service or product.

(D) When accompanied by a Publisher's transfer of copyright agreement (Publisher's Agreement), the Publisher's Agreement is accepted to the extent that the above terms and conditions are consistent with the Publisher's Agreement terms and conditions. The above terms and conditions shall prevail over any inconsistency with the Publisher's Agreement.

Tomiaann Parker  
Authorized Agent  
For Battelle Memorial Institute



Date 3/5/2015



1 Alewife Center #200  
Cambridge, MA 02140  
tel. 617.945.9051  
www.jove.com

## ARTICLE AND VIDEO LICENSE AGREEMENT

Title of Article: Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating

Author(s): Wang, Huamin; Elliott, Douglas C.; French, Richard; Deutch, Steve; Ilsa, Kristiina

Item 1 (check one box): The Author elects to have the Materials be made available (as described at <http://www.jove.com/publish>) via: ☐ Standard Access ☐ Open Access

Item 2 (check one box):

- ☒ The Author is NOT a United States government employee.
- ☐ The Author is a United States government employee and the Materials were prepared in the course of his or her duties as a United States government employee.
- ☐ The Author is a United States government employee but the Materials were NOT prepared in the course of his or her duties as a United States government employee.

### ARTICLE AND VIDEO LICENSE AGREEMENT

1. **Defined Terms.** As used in this Article and Video License Agreement, the following terms shall have the following meanings: "Agreement" means this Article and Video License Agreement; "Article" means the article specified on the last page of this Agreement, including any associated materials such as texts, figures, tables, artwork, abstracts, or summaries contained therein; "Author" means the author who is a signatory to this Agreement; "Collective Work" means a work, such as a periodical issue, anthology or encyclopedia, in which the Materials in their entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole; "CRC License" means the Creative Commons Attribution-Non Commercial-No Derivs 3.0 Unported Agreement, the terms and conditions of which can be found at: <http://creativecommons.org/licenses/by-nc-nd/3.0/legalcode>; "Derivative Work" means a work based upon the Materials or upon the Materials and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation, or any other form in which the Materials may be recast, transformed, or adapted; "Institution" means the institution, listed on the last page of this Agreement, by which the Author was employed at the time of the creation of the Materials; "JoVE" means MyJoVE Corporation, a Massachusetts corporation and the publisher of *The Journal of Visualized Experiments*; "Materials" means the Article and / or the Video; "Parties" means the Author and JoVE; "Video" means any video(s) made by the Author, alone or in conjunction with any other parties, or by JoVE or its affiliates or agents, individually or in collaboration with the Author or any other parties, incorporating all or any portion of the Article, and in which the Author may or may not appear.

2. **Background.** The Author, who is the author of the Article, in order to ensure the dissemination and protection of the Article, desires to have the JoVE publish the Article and create and transmit videos based on the Article. In furtherance of such goals, the Parties desire to memorialize in this Agreement the respective rights of each Party in and to the Article and the Video.

3. **Grant of Rights in Article.** In consideration of JoVE agreeing to publish the Article, the Author hereby grants to JoVE, subject to Sections 4 and 7 below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Article in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Article into other languages, create adaptations, summaries or extracts of the Article or other Derivative Works (including, without limitation, the Video) or Collective Works based on all or any portion of the Article and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. If the "Open Access" box has been checked in Item 1 above, JoVE and the Author hereby grant to the public all such rights in the Article as provided in, but subject to all limitations and requirements set forth in, the CRC License.

## ARTICLE AND VIDEO LICENSE AGREEMENT

4. Retention of Rights in Article. Notwithstanding the exclusive license granted to JoVE in Section 3 above, the Author shall, with respect to the Article, retain the non-exclusive right to use all or part of the Article for the non-commercial purpose of giving lectures, presentations or teaching classes, and to post a copy of the Article on the Institution's website or the Author's personal website, in each case provided that a link to the Article on the JoVE website is provided and notice of JoVE's copyright in the Article is included. All non-copyright intellectual property rights in and to the Article, such as patent rights, shall remain with the Author.

5. Grant of Rights in Video -- Standard Access. This Section 5 applies if the "Standard Access" box has been checked in Item 1 above or if no box has been checked in Item 1 above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby acknowledges and agrees that, Subject to Section 7 below, JoVE is and shall be the sole and exclusive owner of all rights of any nature, including, without limitation, all copyrights, in and to the Video. To the extent that, by law, the Author is deemed, now or at any time in the future, to have any rights of any nature in or to the Video, the Author hereby disclaims all such rights and transfers all such rights to JoVE.

6. Grant of Rights in Video -- Open Access. This Section 6 applies only if the "Open Access" box has been checked in Item 1 above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby grants to JoVE, subject to Section 7 below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Video in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Video into other languages, create adaptations, summaries or extracts of the Video or other Derivative Works or Collective Works based on all or any portion of the Video and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. For any Video to which this Section 6 is applicable, JoVE and the Author hereby grant to the public all such rights in the Video as provided in, but subject to all limitations and requirements set forth in, the CRC License.

7. Government Employees. If the Author is a United States government employee and the Article was prepared in the course of his or her duties as a United States government employee, as indicated in Item 2 above, and any of the licenses or grants granted by the Author hereunder exceed the scope of the 17 U.S.C. 403, then the rights granted hereunder shall be limited to the maximum rights permitted under such

statute. In such case, all provisions contained herein that are not in conflict with such statute shall remain in full force and effect, and all provisions contained herein that do so conflict shall be deemed to be amended so as to provide to JoVE the maximum rights permissible within such statute.

8. Likeness, Privacy, Personality. The Author hereby grants JoVE the right to use the Author's name, voice, likeness, picture, photograph, image, biography and performance in any way, commercial or otherwise, in connection with the Materials and the sale, promotion and distribution thereof. The Author hereby waives any and all rights he or she may have, relating to his or her appearance in the Video or otherwise relating to the Materials, under all applicable privacy, likeness, personality or similar laws.

9. Author Warranties. The Author represents and warrants that the Article is original, that it has not been published, that the copyright interest is owned by the Author (or, if more than one author is listed at the beginning of this Agreement, by such authors collectively) and has not been assigned, licensed, or otherwise transferred to any other party. The Author represents and warrants that the author(s) listed at the top of this Agreement are the only authors of the Materials. ~~If more than one author is listed at the top of this Agreement and if any such author has not entered into a separate Article and Video License Agreement with JoVE relating to the Materials, the Author represents and warrants that the Author has been authorized by each of the other such authors to execute this Agreement on his or her behalf and to bind him or her with respect to the terms of this Agreement as if each of them had been a party hereto as an Author.~~ The Author warrants that the use, reproduction, distribution, public or private performance or display, and/or modification of all or any portion of the Materials does not and will not violate, infringe and/or misappropriate the patent, trademark, intellectual property or other rights of any third party. The Author represents and warrants that it has and will continue to comply with all government, institutional and other regulations, including, without limitation all institutional, laboratory, hospital, ethical, human and animal treatment, privacy, and all other rules, regulations, laws, procedures or guidelines, applicable to the Materials, and that all research involving human and animal subjects has been approved by the Author's relevant institutional review board.

10. JoVE Discretion. If the Author requests the assistance of JoVE in producing the Video in the Author's facility, the Author shall ensure that the presence of JoVE employees, agents or independent contractors is in accordance with the relevant regulations of the Author's institution. If more than one author is listed at the beginning of this Agreement, JoVE may, in its sole discretion, elect not take any action with respect to the Article until such time as it has received complete, executed Article and Video License Agreements from each such author. JoVE reserves the right, in its absolute and sole discretion and without giving any reason therefore, to accept or decline any work submitted to JoVE. JoVE and its employees, agents and independent contractors shall have

## ARTICLE AND VIDEO LICENSE AGREEMENT

full, unfettered access to the facilities of the Author or of the Author's institution as necessary to make the Video, whether actually published or not. JoVE has sole discretion as to the method of making and publishing the Materials, including, without limitation, to all decisions regarding editing, lighting, filming, timing of publication, if any, length, quality, content and the like.

**11. Indemnification.** ~~The Author agrees to indemnify JoVE and/or its successors and assigns from and against any and all claims, costs, and expenses, including attorney's fees, arising out of any breach of any warranty or other representations contained herein. The Author further agrees to indemnify and hold harmless JoVE from and against any and all claims, costs, and expenses, including attorney's fees, resulting from the breach by the Author of any representation or warranty contained herein or from allegations or instances of violation of intellectual property rights, damage to the Author's or the Author's institution's facilities, fraud, libel, defamation, research, equipment, experiments, property damage, personal injury, violations of institutional, laboratory, hospital, ethical, human and animal treatment, privacy or other rules, regulations, laws, procedures or guidelines, liabilities and other losses or damages related in any way to the submission of work to JoVE, making of videos by JoVE, or publication in JoVE or elsewhere by JoVE. The Author shall be responsible for, and shall hold JoVE harmless from, damages caused by lack of sterilization, lack of cleanliness or by contamination due to the making of a video by JoVE, its employees, agents or independent contractors. All sterilization, cleanliness or decontamination procedures shall be solely the responsibility of the Author and shall be undertaken at the Author's~~


~~expense. All indemnifications provided herein shall include JoVE's attorney's fees and costs related to said losses or damages. Such indemnification and holding harmless shall include such losses or damages incurred by, or in connection with, acts or omissions of JoVE, its employees, agents or independent contractors.~~

**12. Fees.** To cover the cost incurred for publication, JoVE must receive payment before production and publication the Materials. Payment is due in 21 days of invoice. Should the Materials not be published due to an editorial or production decision, these funds will be returned to the Author. Withdrawal by the Author of any submitted Materials after final peer review approval will result in a US\$1,200 fee to cover pre-production expenses incurred by JoVE. If payment is not received by the completion of filming, production and publication of the Materials will be suspended until payment is received.

**13. Transfer, Governing Law.** This Agreement may be assigned by JoVE and shall inure to the benefits of any of JoVE's successors and assignees. This Agreement shall be governed and construed by the internal laws of the Commonwealth of Massachusetts without giving effect to any conflict of law provision thereunder. This Agreement may be executed in counterparts, each of which shall be deemed an original, but all of which together shall be deemed to me one and the same agreement. A signed copy of this Agreement delivered by facsimile, e-mail or other means of electronic transmission shall be deemed to have the same legal effect as delivery of an original signed copy of this Agreement.

A signed copy of this document must be sent with all new submissions. Only one Agreement required per submission.

### CORRESPONDING AUTHOR:

Name:	John Stolpa, Associate General Counsel-IP and authorized signatory for Alliance	
Department:	NREL Office of General Counsel	
Institution:	Alliance for Sustainable Energy, LLC	
Article Title:	Biomass Conversion to Produce Hydrocarbon Liquid Fuel via Hot-Vapor-Filtered Fast Pyrolysis and Catalytic Hydrotreating	
Signature:		Date: 3/3/15

Please submit a signed and dated copy of this license by one of the following three methods:

- 1) Upload a scanned copy of the document as a pdf on the JoVE submission site;
- 2) Fax the document to +1.866.381.2236;
- 3) Mail the document to JoVE / Attn: JoVE Editorial / 1 Alewife Center #200 / Cambridge, MA 02139

For questions, please email [submissions@jove.com](mailto:submissions@jove.com) or call +1.617.945.9051

Authorization for Alliance employees only!

\* The Alliance for Sustainable Energy, LLC (Alliance) is the manager and operator of the National Renewable Energy Laboratory (NREL)

\*\*Employees of the Alliance for Sustainable Energy, LLC, under Contract No. DE-AC36-08GO28308 with the U.S. Dept. of Energy have authored this work. The United States Government retains and the publisher, by accepting the article for publication, acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for United States Government purposes.

**Editorial comments:**

Some minor revisions are required before formal acceptance can occur:

[Thanks for the comments.](#)

1. Please provide a superscripted reference for steps 1.11.3 and 2.2.4.

[Reply: More details on the step have been added.](#)

2. Please explicitly discuss limitations of the technique in the Discussion.


[Reply: More discussion on the limitations of the technique have been added.](#)



[Click here to access/download](#)

**Supplemental File (as requested by JoVE)**  
renamed\_5bf46.pdf





[Click here to access/download](#)

**Supplemental File (as requested by JoVE)**  
Supplemental files.docx

