

Journal of Visualized Experiments

Design and Fabrication of an Optical fiber made of Water.

--Manuscript Draft--

Article Type:	Invited Methods Article - JoVE Produced Video
Manuscript Number:	JoVE58174R2
Full Title:	Design and Fabrication of an Optical fiber made of Water.
Keywords:	Fiber optics; Micro-optics; Optofluidics; Optomechanics; MEMS; Microelectromechanical systems; Microelectrocapillary systems; MECS; Optocapillaries.
Corresponding Author:	Mark Douvidzon ISRAEL
Corresponding Author's Institution:	
Corresponding Author E-Mail:	mark.douvidzon@campus.technion.ac.il
Order of Authors:	Mark Douvidzon Shai Maayani Leopoldo L. Martin Tal Carmon
Additional Information:	
Question	Response
Please indicate whether this article will be Standard Access or Open Access.	Standard Access (US\$2,400)
Please indicate the city, state/province, and country where this article will be filmed . Please do not use abbreviations.	Optomechanics Lab (Tal Carmon), 3rd Floor, Dan Kahn Bldg, Technion City, 3200003, Israel

TITLE:

Design and Fabrication of an Optical Fiber Made of Water

AUTHORS & AFFILIATIONS:

Mark L. Douvidzon¹, Shai Maayani², Leopoldo L. Martin³, Tal Carmon⁴

¹Department of Nanoscience and Nanotechnology, Russell Berrie Nanotechnology Institute (RBNI), Technion - Israel Institute of Technology, Haifa, Israel

²Department of Material Sciences and Engineering, MIT, Cambridge, USA

³Centro de Tecnologia Nanofotónica, Universitat Politècnica de València, Valencia, Spain

⁴Department of Mechanical Engineering, Technion - Israel Institute of Technology, Haifa, Israel

Corresponding Author:

Mark Douvidzon (Mark.Douvidzon@technion.ac.il)

E-mail Addresses of the Co-authors:

Shai Maayani (shay.maayani@gmail.com)

Leopoldo L. Martin (astroleopoldo@gmail.com)

Tal Carmon (tal.carmon@gmail.com)

KEYWORDS:

Fiber optics, micro-optics, optofluidics, optomechanics, MEMS, MECS, optocapillaries

SHORT ABSTRACT:

This protocol describes the design and manufacture of a water bridge and its activation as a water fiber. The experiment demonstrates that capillary resonances of the water fiber modulate its optical transmission.

LONG ABSTRACT:

In this report, an optical fiber of which the core is made solely of water, while the cladding is air, is designed and manufactured. In contrast with solid-cladding devices, capillary oscillations are not restricted, allowing the fiber walls to move and vibrate. The fiber is constructed by a high direct current (DC) voltage of several thousand volts (kV) between two water reservoirs that creates a floating water thread, known as a water bridge. Through the choice of micropipettes, it is possible to control the maximal diameter and length of the fiber. Optical fiber couplers, at both sides of the bridge, activate it as an optical waveguide, allowing researchers to monitor the water fiber capillary body waves through transmission modulation and, therefore, deducing changes in surface tension.

Co-confining two important wave types, capillary and electromagnetic, opens a new path of research in the interactions between light and liquid-wall devices. Water-walled microdevices are a million times softer than their solid counterparts, accordingly improving the response to minute forces.

INTRODUCTION:

Since the breakthrough of optical fibers in communication, awarded with a Nobel prize in 2009¹, a series of fiber-based applications grew alongside. Nowadays, fibers are a necessity in laser surgeries², as well as in coherent X-ray generation^{3,4}, guided-sound⁵ and supercontinuum⁶. Naturally, the research on fiber optics expanded from utilizing solids into exploiting liquids for optical wave guiding, where liquid-filled microchannels and laminar flow combine the transportation properties of a liquid with the advantages of optical interrogation⁷⁻⁹. However, these devices clamp the liquid between solids and, therefore, forbid it to express its own wave character, known as capillary wave.

Capillary waves, similar to those seen when throwing a stone into a pond, are an important wave in nature. However, due to the obstacles of controlling a liquid without dampening its surface through channels or solids, they are hardly utilized for detection or application. In contrast, the device presented in this protocol has no solid boundaries; it is surrounded by and flows in air, allowing, therefore, capillary waves to develop, propagate, and interact with light.

To fabricate a water fiber, it is necessary to go back to a technique known as the floating water bridge, first reported in 1893¹⁰, where two beakers filled with distilled water and connected to a high-voltage source will form a fluidic, water thread-like connection between them¹¹. Water bridges can reach up to a length of 3 cm¹² or be as thin as 20 nm¹³. As for the physical origin, it has been shown that surface tensions, as well as dielectric forces, are both responsible for carrying the bridge's weight¹⁴⁻¹⁶. To activate the water bridge as a water fiber, we couple light in with an adiabatically tapered silica fiber^{17,18} and out with a silica fiber lens¹⁹. Such a device can host acoustical, capillary, and optical waves, making it advantageous for multi-wave detectors and lab-on-chip²⁰⁻²² applications.

PROTOCOL:

CAUTION: This experiment involves high voltage. It is the reader's responsibility to verify with the safety authorities that their experiment follows regulations before turning on the high voltage.

Note: Any kind of polar liquid can be utilized to produce liquid fibers, such as ethanol, methanol, acetone, or water. The polarity of the liquid dictates the stability and diameter of the created fiber^{23,24}. For best results, use deionized water with 18 M Ω resistance. Before choosing optical components, such as optical fibers and light sources, consult the literature to ensure a low absorption in the water/liquid fiber at the desired optical wavelength. The protocol can be paused at any given moment before filling the water reservoir (step 4.5).

1. Preparation of Water Reservoirs and Experimental Station

1.1. Manufacture two poly(methyl methacrylate) (PMMA) reservoirs with magnetic connectors for the pipette and the high voltage, according to **Figure 1**.

1.1.1. Cut two PMMA plates to 60 x 50 x 10 mm in size, drill cavities of 8 mm in depth and 7 mm in diameter on the backside of the plates. Glue connector magnets inside the cavities.

1.1.2. For the capillary clamp, cut a stripe of PMMA to 45 x 10 x 2 mm and glue two magnets on the top side of it.

1.1.3. For the electric connector, wrap magnets in a small piece of metallic foil and connect it electrically with crocodile clamps to the high-voltage (HV) source. The reservoirs hold approximately 100 - 300 μ L of water. Place the wrapped magnets in fluidic contact with the water in the reservoir.

Note: Preferably, use magnetic connectors for clamps and high voltage. If possible, do not use any kind of glue to attach the clamps or the connectors, as many types of glues dissolve under the influence of high voltage or in the presence of electric arcs and diminish the water fiber stability or optical quality.

1.2. Mount one PMMA reservoir on a 5-degree-of-freedom (DOF) micro-positioning stage.

1.3. Thoroughly clean all connectors and areas with isopropanol (spectral grade) followed by deionized water. Blow-dry with nitrogen. Cover the PMMA water reservoir and all clamps with polytetrafluoroethylene (PTFE) tape to avoid any leaking or dripping of water.

1.4. Position the set-up under an optical microscope for imaging. Use far-field objectives (5X, 0.14 NA, and 34 mm WD for long water fibers and 20X, 0.42 NA, and 20 mm WD lens for short water fibers) to avoid unwanted grounding between the HV area of the water fiber and the electrically conductive microscope set-up.

1.5. Set up two optical fiber clamps on linear transitional stages, one behind each water reservoir, according to **Figure 1**. Each fiber coupler should be able to move back and forward within its micropipette (discussed in the following section).

2. Choosing the Micropipettes and Voltage

2.1. The inner diameter of the micropipette ensures a maximum radius of the fabricated water fiber. To create a 5- μ m radius water fiber, use 150- μ m-inner-diameter pipettes, paired with 125- μ m-diameter optical fibers. For thicker (20 - 90 μ m) and longer (800 - 1,000 μ m) water fibers, use micropipettes with an inner diameter of 850 μ m.

Note: As a rule of thumb, the water fiber maximum length is estimated by multiplying the maximal radius by 25. For details, refer to **Table 1**.

2.1.1. Break the micropipette by hand over an edge to a length of 3 cm.

2.2. To create water fibers with a diameter of up to 110 μm , apply a voltage between the two water reservoirs between 1.5 kV and 3 kV. For water fibers reaching up to a millimeter in length, apply up to 8 kV. Compare with **Figure 1** for electrical wiring suggestions.

3. Preparation of the Optical Couplers

Note: For the best transmission result, use a single-mode tapered fiber to launch laser light into the water fiber and a highly multimode reflowed fiber lens as the output coupler (core > 100 μm). However, for easy operation, use a low multimode fiber as the output coupler (for example, a 1550-nm single-mode fiber for a 780-nm wavelength).

3.1. Fabrication of a Tapered Fiber Coupler

Note: See **Figure 2**.

3.1.1. Strip the 780-nm single-mode fiber with a fiber stripper from its plastic cladding to expose an area of 10 - 15 mm of bare fiber. Clean the exposed area with delicate task wipes in combination with acetone. Pass the fiber through the desired micropipette before tapering it. Taper the fiber below the single-mode criteria with a slope smaller than 1/20.

3.1.2. Use a hydrogen flame for tapering the fiber with a flow rate of 140 mL/min, while simultaneously pulling the taper from both sides at 0.06 mm/s.

Note: The tapered portion is in total between 6 to 9 mm. If the fiber breaks before reaching the single-mode criteria, adjust the hydrogen flow to higher rates or place the fiber in a hotter area of the torch. If the area is longer, adjust the hydrogen flow to lower rates or place the fiber in a colder area of the torch.

3.1.3. Turn off the flame and carefully increase the tension in the fiber until it breaks at its thinnest spot. Use this tapered fiber as the input coupler.

CAUTION: The tapered fiber is fragile.

3.2. Fabrication of a Fiber Lens Coupler

3.2.1. Strip the 1550-nm single-mode fiber tip with a fiber stripper and clean the exposed area with delicate task wipes in combination with acetone. Choose and prepare a pipette as described above and pass the fiber through it.

3.2.2. Heat the tip with an electric fusion splicer or CO₂ laser at 15-W power, focused through a 200-mm lens, until the glass fiber end becomes liquid and forms a slightly rounded shape, known as a fiber lens.

4. Assembling

176
177 4.1. If not done yet, insert the fiber couplers into the desired micropipettes.
178

179 4.2. Clamp the micropipette, using the premanufactured, magnetic PMMA clamp, with the fiber
180 couplers onto the PMMA reservoirs. The non-tapered side of the micropipettes should reach into
181 the water reservoir. Clamp each of the fiber couplers on a linear positioning stage.
182

183 4.3. Connect the tapered fiber coupler to a 780-nm, continuous wave, fiber-coupled 10-mW laser
184 source and the fiber lens coupler to a power meter. Fill the reservoir with water and ensure that
185 no air bubbles are stuck in the micropipette. If necessary, push or pull them with the optical fiber
186 coupler (from step 3.1 or, accordingly, from step 3.2).
187

188 Note: At this stage, following the optical path, the stations are: the laser light source, the optical
189 fiber, (and this fiber goes through) the fiber clamp on a linear stage, the water in the reservoir
190 with electrical connection, the micropipette filled with water, the optical tapered fiber coupler,
191 free space (later: water fiber), the fiber lens coupler (now the second fiber), the micropipette
192 filled with water, the water reservoir with electric connection, the fiber clamp on a linear stage,
193 and, lastly, the power meter.
194

195 4.4. Connect the ends of the mounted micropipettes by adjusting the 5-degre-of-freedom mount
196 of the PMMA water reservoir to establish a fluidic contact between the micropipettes. Turn on
197 the light source and the power meter. Adjust the fiber couplers to have a transmission with the
198 help of the 5-DOF PMMA water reservoir mount.
199

200 Note: Use appropriate laser safety equipment.
201

202 4.5. Connect the high voltage electrically with the water reservoir by placing the magnetic
203 connectors wrapped in metallic foil over the magnetic counterparts in the PMMA water reservoir
204 and attaching crocodile clamps to the metallic foil. Connect the crocodile clamps *via* electrical
205 cables to the HV source (**Figure 2a**).
206

207 **5. Running the Experiment** 208

209 5.1. Increase the voltage to the desired value. A starting point for a very short and narrow bridge
210 is 1.5 kV. Stable bridges with 100 μm and more in length can be achieved with 2.5 - 3 kV.
211

212 5.2. Slowly increase the distance between the micropipettes to the desired length according to
213 the choice of the micropipettes (**Figures 2b** and **2c**). Adjust couplers and pipettes with the 5-DOF
214 stage and the 1-DOF stages to optimize the optical transmission.
215

216 5.3. Measure the coupling efficiency by taking a measurement on the power meter and taking
217 the ratio of the coupled-in to the coupled-out laser power.
218

5.4. Disconnect the power meter and connect a photoreceiver to the output fiber coupler. Connect the photoreceiver to an oscilloscope. Record time trace measurements of the transmitted light, representing the capillary water fiber oscillations.

5.5. Convert the time trace measurements *via* Fast Fourier Transformation to frequency domain. Take the central frequency over full width at half maximum to receive the capillary quality factor.

Note: Create a spectrogram to check for frequency jitter.

5.6. Use the top view microscope set-up to characterize the geometrical structure of the water fiber. The fiber radius is obtained at the thinnest portion of the water fiber.

REPRESENTATIVE RESULTS:

The coupling efficiency from a water fiber to a highly multimode fiber can be as high as 54%^{25,26}. The coupling efficiency to a single-mode fiber is up to 12%^{25,26}. Water fibers can be as thin as 1.6 μm in diameter and can have a length of 46 μm (**Figure 3**)^{25,26}, or they can be up to 1.064 mm in length with a diameter of 41 μm (**Figure 3**)^{25,26}. The transmission spectrogram reveals capillary oscillation of the water fiber, similar to that of a guitar string (**Figure 4**)^{25,26}. The capillary quality factors were estimated to be as high as 14 for long fibers^{25,26}. Considering the theory on water bridges, it is possible to estimate the ratio between the surface tension and the dielectric force^{25,26}.

FIGURE AND TABLE LEGENDS:

Figure 1: Schematics of the set-up. (a) This illustration shows the water fiber experimental set-up. (b) This sketch shows the water reservoir, the electrical connector, and the pipette clamp. (c) This panel shows the water-walled waveguide softness compared with common solids. This figure is reproduced in part from Douvidzon *et al.*^{25,26}.

Figure 2: Set-up photos. (a) This panel shows the PMMA-water reservoir on a 5-DOF mount. with the PMMA-pipette clamp, the micropipette, the optical fiber, and the electric connector. (b) This panel shows that a fluidic contact between the micropipettes is created. (c) This panel shows that the distance between the micropipettes is increased to establish a water fiber.

Figure 3: Water fiber characterization. (a) This panel shows a water fiber longer than 1 mm. The next two panels show (b) a micron-scale-thin water fiber, (c) the surface scattering due to capillary waves at the water fiber liquid-phase boundary. (d) This panel shows light propagation through the water fiber volume confirmed by a fluorescent dye measurement. This figure is reproduced from Douvidzon *et al.*^{25,26}.

Figure 4: Experimentally measuring the water fiber “guitar-string” modes. (a) This panel shows a time trace measurement. (b) A fluctuation spectrum reveals a fundamental mode and, at integer multiplications, its three overtones (dash lines). (c) This panel shows a fluctuation spectrogram of a 0.94-mm-long fiber with changing voltage and, correspondingly, changing the

fiber diameter, with voltage first constant, then increased, and finally, decreased. The color code describes the transmission. (d) This panel shows the fundamental frequency of the fiber as a function of the fiber diameter (circles) together with a theoretical prediction (dashed line). Horizontal and vertical error bars represent the uncertainty of eight consecutive, 250-ms-apart measurements of the central frequency and its corresponding fiber diameter. For all panels, the fiber length is 0.94 mm and the oscillation is optically interrogated with a photodetector. The diameter is measured *via* microscope. This figure is reproduced from Douvidson *et al.*^{25,26}.

Table 1: Water fiber length and radius. This table shows the water fiber length and radius with respect to the electric potential and the pipette diameter. This table is reproduced from Douvidson, *et al.*²⁵.

DISCUSSION:

To conclude, the major advantage and uniqueness of this technique is creating a fiber which hosts three different kinds of waves: capillary, acoustic, and optical. All three waves oscillate in different regimes, opening the possibility for multi-wave detectors. As an example, airborne nanoparticles affect the surface tension of liquids. Already at the current stage, it is possible to monitor changes in the surface tension through variations in the capillary eigenfrequency. Additionally, water-walled devices are a million times softer than their solid counterparts, improving the sensibility of sensors accordingly.

Based on experience with this set-up, we noticed a high dependency on the signal-to-noise ratio and the quality of the optical couplers. Therefore, it is recommended to pay close attention to the fabrication of the optical couplers. Consider an aquarium set-up to ensure a dust-free environment for the tapering station and the water fiber set-up. Also, the execution of the experiment involves a risk of breaking or damaging the tapered fiber coupler mechanically or through an electric arc. In that case, the optical transmission can drop and become noisy to such an extent that the capillary modes of the fiber are no longer visible in the spectrogram.

If capillary waves are not visible in the transmission measurements, remanufacture the couplers. Additionally, the water fiber and the optical fiber couplers do not attract each other. Adjusting the set-up for optimal transmission may require putting the water fiber a bit askew, to mechanically press the tapered fiber coupler inside the water fiber.

Another obstacle in this set-up to be aware of is the crucial electrical resistivity of the water. Even small amounts of ions in the liquid will cause the bridge to collapse. If the water fiber is shorter and less stable than expected, a contamination of the water might be the cause. Replace the water with 18 M Ω clean room water. Additionally, the high voltage attracts charged air particles in the surrounding of the water fiber, which dissolve and contribute to the instability. In this case, a closed chamber will help improve the water fiber longevity.

An outstanding aspect of this set-up is that any polar liquid can be utilized to create a liquid fiber, although deionized water is known for creating the longest, as well as, time-wise, the most stable water fibers. It is interesting to consider other liquids for different applications. Switching the

water to a liquid or a mix of polar liquids with fitting viscosity, surface tension, or optical properties allows researchers to trim the fiber exactly to their demands.

ACKNOWLEDGMENTS:

This research was supported by the Israeli Ministry of Science, Technology & Space; ICore: the Israeli Excellence center 'Circle of Light' grant no. 1902/12, and by the Israeli Science Foundation grant no. 2013/15. The authors thank Karen Adie Tankus (KAT) for the helpful editing.

DISCLOSURES:

The authors have nothing to disclose.

REFERENCES:

1. Kao, C. K., Boyle, W. S., Smith, G. E. 'For Groundbreaking Achievements Concerning the Transmission of Light in Fibers for Optical Communication'. *The Nobel Prize in Physics*. http://www.nobelprize.org/nobel_prizes/physics/Laureates/2009/kao-facts.html (2009).
2. Temelkuran, B., Hart, S. D., Benoit, G., Joannopoulos, J. D., Fink, Y. Wavelength-scalable hollow optical fibres with large photonic bandgaps for CO₂ laser transmission. *Nature*. **420**, 650-653 (2002).
3. Rundquist, A. Phase-Matched Generation of Coherent Soft X-rays. *Science*. **280**, 1412-1415 (1998).
4. Durfee, C. G. *et al.* Phase Matching of High-Order Harmonics in Hollow Waveguides. *Physical Review Letters*. **83**, 2187-2190 (1999).
5. Dainese, P. *et al.* Stimulated Brillouin scattering from multi-GHz-guided acoustic phonons in nanostructured photonic crystal fibres. *Nature Physics*. **2**, 388-392 (2006).
6. Dudley, J. M. J., Genty, G., Coen, S. Supercontinuum generation in photonic crystal fiber. *Reviews of Modern Physics*. **78**, 1135-1184 (2006).
7. Wolfe, D. B. *et al.* Dynamic control of liquid-core/Liquid-cladding optical waveguides. *Proceedings of the National Academy of Sciences of the United States of America*. **101**, 12434-12438 (2004).
8. Whitesides, G. M. The origins and the future of microfluidics. *Nature*. **442**, 368-373 (2006).
9. Ward, J. M., Yang, Y., Chormaic, S. N. Highly Sensitive Temperature Measurements With Liquid-Core Microbubble Resonators. *IEEE Photonics Technology Letters*. **25**, 2350-2353 (2013).
10. Armstrong. The Newcastle Literary and Philosophical Society. *The Electrical Engineer*. 154-155. http://ecfuchs.com/waterbridge_jw/Armstron_full_article.pdf. January 19, 2016 (1893).

11. Fuchs, E. E. C. *et al.* The floating water bridge. *Journal of Physics D: Applied Physics*. **40**, 6112-6114 (2007).
12. Fuchs, E. C. *et al.* The Armstrong experiment revisited. *The European Physics Journal Special Topics*. **223**, 959-977 (2013).
13. Sirghi, L., Szoszkiewicz, R., Riedo, E. Volume of a nanoscale water bridge. *Langmuir*. **22**, 1093-1098 (2006).
14. Woisetschläger, J., Gatterer, K., Fuchs, E. C. Experiments in a floating water bridge. *Experiments in Fluids*. **48**, 121-131 (2009).
15. Widom, A., Swain, J., Silverberg, J., Sivasubramanian, S., Srivastava, Y. N. Theory of the Maxwell pressure tensor and the tension in a water bridge. *Physical Review E: Statistical, Nonlinear, and Soft Matter Physics*. **80**, 16301 (2009).
16. Aerov, A. A. Why the water bridge does not collapse. *Physical Review E: Statistical, Nonlinear, and Soft Matter Physics*. **84**, 36314 (2011).
17. Knight, J. C., Cheung, G., Jacques, F., Birks, T. A. Phase-matched excitation of whispering-gallery-mode resonances by a fiber taper. *Optics Letters*. **22**, 1129 (1997).
18. Spillane, S. M., Kippenberg, T. J., Painter, O. J., Vahala, K. J. Ideality in a Fiber-Taper-Coupled Microresonator System for Application to Cavity Quantum Electrodynamics. *Physical Review Letters*. **91**, 43902 (2003).
19. Cohen, L. G., Schneider, M. V. Microlenses for coupling junction lasers to optical fibers. *Applied Optics*. **13**, 89-94 (1974).
20. Vollmer, F. *et al.* Whispering-gallery-mode biosensing: label-free detection down to single molecules. *Nature Methods*. **5**, 591-596 (2008).
21. Fainman, Y., Lee, L. P., Psaltis, D., Yang, C. *Optofluidics: Fundamentals, Devices, and Applications*. McGraw-Hill, Inc. (2010).
22. He, L., Ozdemir, S. K., Zhu, J., Kim, W., Yang, L. Detecting single viruses and nanoparticles using whispering gallery microlasers. *Nature Nanotechnology*. **6**, 428-432 (2011).
23. Woisetschläger, J. *et al.* Horizontal bridges in polar dielectric liquids. *Experiments in Fluids*. **52**, 193-205 (2011).
24. Fuchs, E. C., Wexler, A. D., Agostinho, L. L. F., Ramek, M., Woisetschläger, J. Methanol, Ethanol and Propanol in EHD liquid bridging. *Journal of Physics: Conference Series*. **329**, 12003 (2011).

- 395 25. Douvidzon, M. L., Maayani, S., Martin, L. L., Carmon, T. Light and Capillary Waves Propagation
396 in Water Fibers. *Science Reports*. **7**, 16633 (2017).
397
398 26. Douvidzon, M., Maayani, S., Martin, L. L., Carmon, T. Water Fibers. *Cornell University Library*.
399 <https://arxiv.org/abs/1609.03362> (2016).
400





Figure 3





Figure 4

[Click here to download Figure Figure 4.tif](#)



Click here to access/download
Video or Animated Figure
Figure 1.svg

Pipette's internal diameter			Water fiber		
Lens side [μm]	Taper side [μm]	Potential [V]	Radius [μm]	Length [μm]	
850	850	6000	51	830	Fig. 1b
850	850	6000	20.5	1064	Fig. 2a
850	150	1500	1.6 - 0.8	46	Fig. 2b
850	850	5000	32.5	820	Fig. 2c
150	150	3000	4.75	110	Fig. 2d
850	850	3000 - 8000	20 - 90	940	Fig. 3
850	150	2500	2.7 - 3	24 - 73	Fig. 4

Name of Material/ Equipment	Company
Deioniyzed Water	
Micropipettes, Borosilicate Glass, round, inner diameter 850 micron	Produstrial.com
Micropipettes, Borosilicate Glass, round, inner diameter 150 micron	Produstrial.com
High voltage, low current source, 3kV with 5 mA.	Bertan
High voltage, low current source, 8 kV with 0.25 mA.	Home build
Optical fiber	Corning
Optical fiber	Thorlabs
Optical fiber	Thorlabs
Fiber coupled laser	FIS
Photoreceiver	New Port/ New Focus
Oscilloscope	Agilent Technologies
2 Degree of freedom tilt stagestage	New Port/ New Focus
3Degree of freedom linear micro translation stage	New Port/ New Focus
A set of magnets	
Objective 5X	Mitutoyo
Objective 20 x	Mitutoyo
Zoom	Navitar
Microscope tube	
Isopropanol	Navitar
2 x Bare Fiber holder	Sigma Aldrich
2 x Translational Stage	Thorlabs
Block of PMMA for fabricating the water reservoir and pipette holder	Thorlabs
PTFE-Tape	
Fiber coupled, cw Laser Light Source	Gufero
	New Port/ New Focus

Catalog Number	Comments/Description
#133260	18MOhm resistance
#133258	
Model 215	
HI 780 C	5 meter
FTO 30	5 meter
FTO 30	5 meter
SMF 28E	
1801-FS	with fiber connection
DSO-X 3034A	
M-562F-TILT	
M-562F-XYZ	
MY5X-802	
MY20X-804	
12x Zoom	
1-6015 standard	
tube	
67-63-0	Spec Grad
T711-250	
DT12	
	150 x 60 x 10 mm
240453	
TLB-6712	765-781 nm



1 Alewife Center #200
Cambridge, MA 02140
tel. 617.945.9051
www.jove.com

ARTICLE AND VIDEO LICENSE AGREEMENT

Title of Article:

Design and Fabrication of an Optical Fiber made of Water

Author(s):

Davidson, Magani, Markin, Carmon

Item 1 (check one box): The Author elects to have the Materials be made available (as described at <http://www.jove.com/author>) via: ☒ Standard Access ☐ Open Access

Item 2 (check one box):

- ☒ The Author is NOT a United States government employee.
- ☐ The Author is a United States government employee and the Materials were prepared in the course of his or her duties as a United States government employee.
- ☐ The Author is a United States government employee but the Materials were NOT prepared in the course of his or her duties as a United States government employee.

ARTICLE AND VIDEO LICENSE AGREEMENT

1. **Defined Terms.** As used in this Article and Video License Agreement, the following terms shall have the following meanings: "**Agreement**" means this Article and Video License Agreement; "**Article**" means the article specified on the last page of this Agreement, including any associated materials such as texts, figures, tables, artwork, abstracts, or summaries contained therein; "**Author**" means the author who is a signatory to this Agreement; "**Collective Work**" means a work, such as a periodical issue, anthology or encyclopedia, in which the Materials in their entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole; "**CRC License**" means the Creative Commons Attribution-Non Commercial-No Derivs 3.0 Unported Agreement, the terms and conditions of which can be found at: <http://creativecommons.org/licenses/by-nc-nd/3.0/legalcode>; "**Derivative Work**" means a work based upon the Materials or upon the Materials and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation, or any other form in which the Materials may be recast, transformed, or adapted; "**Institution**" means the institution, listed on the last page of this Agreement, by which the Author was employed at the time of the creation of the Materials; "**JoVE**" means MyJoVE Corporation, a Massachusetts corporation and the publisher of *The Journal of Visualized Experiments*; "**Materials**" means the Article and / or the Video; "**Parties**" means the Author and JoVE; "**Video**" means any video(s) made by the Author, alone or in conjunction with any other parties, or by JoVE or its affiliates or agents, individually or in collaboration with the Author or any other parties, incorporating all or any portion of the Article, and in which the Author may or may not appear.

2. **Background.** The Author, who is the author of the Article, in order to ensure the dissemination and protection of the Article, desires to have the JoVE publish the Article and create and transmit videos based on the Article. In furtherance of such goals, the Parties desire to memorialize in this Agreement the respective rights of each Party in and to the Article and the Video.

3. **Grant of Rights in Article.** In consideration of JoVE agreeing to publish the Article, the Author hereby grants to JoVE, subject to Sections 4 and 7 below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Article in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Article into other languages, create adaptations, summaries or extracts of the Article or other Derivative Works (including, without limitation, the Video) or Collective Works based on all or any portion of the Article and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. If the "Open Access" box has been checked in Item 1 above, JoVE and the Author hereby grant to the public all such rights in the Article as provided in, but subject to all limitations and requirements set forth in, the CRC License.

ARTICLE AND VIDEO LICENSE AGREEMENT

4. Retention of Rights in Article. Notwithstanding the exclusive license granted to JoVE in **Section 3** above, the Author shall, with respect to the Article, retain the non-exclusive right to use all or part of the Article for the non-commercial purpose of giving lectures, presentations or teaching classes, and to post a copy of the Article on the Institution's website or the Author's personal website, in each case provided that a link to the Article on the JoVE website is provided and notice of JoVE's copyright in the Article is included. All non-copyright intellectual property rights in and to the Article, such as patent rights, shall remain with the Author.

5. Grant of Rights in Video – Standard Access. This **Section 5** applies if the "Standard Access" box has been checked in **Item 1** above or if no box has been checked in **Item 1** above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby acknowledges and agrees that, Subject to **Section 7** below, JoVE is and shall be the sole and exclusive owner of all rights of any nature, including, without limitation, all copyrights, in and to the Video. To the extent that, by law, the Author is deemed, now or at any time in the future, to have any rights of any nature in or to the Video, the Author hereby disclaims all such rights and transfers all such rights to JoVE.

6. Grant of Rights in Video – Open Access. This **Section 6** applies only if the "Open Access" box has been checked in **Item 1** above. In consideration of JoVE agreeing to produce, display or otherwise assist with the Video, the Author hereby grants to JoVE, subject to **Section 7** below, the exclusive, royalty-free, perpetual (for the full term of copyright in the Article, including any extensions thereto) license (a) to publish, reproduce, distribute, display and store the Video in all forms, formats and media whether now known or hereafter developed (including without limitation in print, digital and electronic form) throughout the world, (b) to translate the Video into other languages, create adaptations, summaries or extracts of the Video or other Derivative Works or Collective Works based on all or any portion of the Video and exercise all of the rights set forth in (a) above in such translations, adaptations, summaries, extracts, Derivative Works or Collective Works and (c) to license others to do any or all of the above. The foregoing rights may be exercised in all media and formats, whether now known or hereafter devised, and include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. For any Video to which this **Section 6** is applicable, JoVE and the Author hereby grant to the public all such rights in the Video as provided in, but subject to all limitations and requirements set forth in, the CRC License.

7. Government Employees. If the Author is a United States government employee and the Article was prepared in the course of his or her duties as a United States government employee, as indicated in **Item 2** above, and any of the licenses or grants granted by the Author hereunder exceed the scope of the 17 U.S.C. 403, then the rights granted hereunder shall be limited to the maximum rights permitted under such

statute. In such case, all provisions contained herein that are not in conflict with such statute shall remain in full force and effect, and all provisions contained herein that do so conflict shall be deemed to be amended so as to provide to JoVE the maximum rights permissible within such statute.

8. Likeness, Privacy, Personality. The Author hereby grants JoVE the right to use the Author's name, voice, likeness, picture, photograph, image, biography and performance in any way, commercial or otherwise, in connection with the Materials and the sale, promotion and distribution thereof. The Author hereby waives any and all rights he or she may have, relating to his or her appearance in the Video or otherwise relating to the Materials, under all applicable privacy, likeness, personality or similar laws.

9. Author Warranties. The Author represents and warrants that the Article is original, that it has not been published, that the copyright interest is owned by the Author (or, if more than one author is listed at the beginning of this Agreement, by such authors collectively) and has not been assigned, licensed, or otherwise transferred to any other party. The Author represents and warrants that the author(s) listed at the top of this Agreement are the only authors of the Materials. If more than one author is listed at the top of this Agreement and if any such author has not entered into a separate Article and Video License Agreement with JoVE relating to the Materials, the Author represents and warrants that the Author has been authorized by each of the other such authors to execute this Agreement on his or her behalf and to bind him or her with respect to the terms of this Agreement as if each of them had been a party hereto as an Author. The Author warrants that the use, reproduction, distribution, public or private performance or display, and/or modification of all or any portion of the Materials does not and will not violate, infringe and/or misappropriate the patent, trademark, intellectual property or other rights of any third party. The Author represents and warrants that it has and will continue to comply with all government, institutional and other regulations, including, without limitation all institutional, laboratory, hospital, ethical, human and animal treatment, privacy, and all other rules, regulations, laws, procedures or guidelines, applicable to the Materials, and that all research involving human and animal subjects has been approved by the Author's relevant institutional review board.

10. JoVE Discretion. If the Author requests the assistance of JoVE in producing the Video in the Author's facility, the Author shall ensure that the presence of JoVE employees, agents or independent contractors is in accordance with the relevant regulations of the Author's institution. If more than one author is listed at the beginning of this Agreement, JoVE may, in its sole discretion, elect not take any action with respect to the Article until such time as it has received complete, executed Article and Video License Agreements from each such author. JoVE reserves the right, in its absolute and sole discretion and without giving any reason therefore, to accept or decline any work submitted to JoVE. JoVE and its employees, agents and independent contractors shall have

ARTICLE AND VIDEO LICENSE AGREEMENT

full, unfettered access to the facilities of the Author or of the Author's institution as necessary to make the Video, whether actually published or not. JoVE has sole discretion as to the method of making and publishing the Materials, including, without limitation, to all decisions regarding editing, lighting, filming, timing of publication, if any, length, quality, content and the like.

11. **Indemnification.** The Author agrees to indemnify JoVE and/or its successors and assigns from and against any and all claims, costs, and expenses, including attorney's fees, arising out of any breach of any warranty or other representations contained herein. The Author further agrees to indemnify and hold harmless JoVE from and against any and all claims, costs, and expenses, including attorney's fees, resulting from the breach by the Author of any representation or warranty contained herein or from allegations or instances of violation of intellectual property rights, damage to the Author's or the Author's institution's facilities, fraud, libel, defamation, research, equipment, experiments, property damage, personal injury, violations of institutional, laboratory, hospital, ethical, human and animal treatment, privacy or other rules, regulations, laws, procedures or guidelines, liabilities and other losses or damages related in any way to the submission of work to JoVE, making of videos by JoVE, or publication in JoVE or elsewhere by JoVE. The Author shall be responsible for, and shall hold JoVE harmless from, damages caused by lack of sterilization, lack of cleanliness or by contamination due to the making of a video by JoVE its employees, agents or independent contractors. All sterilization, cleanliness or decontamination procedures shall be solely the responsibility of the Author and shall be undertaken at the Author's

expense. All indemnifications provided herein shall include JoVE's attorney's fees and costs related to said losses or damages. Such indemnification and holding harmless shall include such losses or damages incurred by, or in connection with, acts or omissions of JoVE, its employees, agents or independent contractors.

12. **Fees.** To cover the cost incurred for publication, JoVE must receive payment before production and publication the Materials. Payment is due in 21 days of invoice. Should the Materials not be published due to an editorial or production decision, these funds will be returned to the Author. Withdrawal by the Author of any submitted Materials after final peer review approval will result in a US\$1,200 fee to cover pre-production expenses incurred by JoVE. If payment is not received by the completion of filming, production and publication of the Materials will be suspended until payment is received.

13. **Transfer, Governing Law.** This Agreement may be assigned by JoVE and shall inure to the benefits of any of JoVE's successors and assignees. This Agreement shall be governed and construed by the internal laws of the Commonwealth of Massachusetts without giving effect to any conflict of law provision thereunder. This Agreement may be executed in counterparts, each of which shall be deemed an original, but all of which together shall be deemed to me one and the same agreement. A signed copy of this Agreement delivered by facsimile, e-mail or other means of electronic transmission shall be deemed to have the same legal effect as delivery of an original signed copy of this Agreement.

A signed copy of this document must be sent with all new submissions. Only one Agreement required per submission.

CORRESPONDING AUTHOR:

Name: Mark Davidzon
Department: Nanoscience and Nanotechnology - RBNi
Institution: Technion - Institut of Technology
Article Title: Design and Fabrication of an Optical Fiber made of Water
Signature: Davidzon Date: 20.03.18

Please submit a **signed** and **dated** copy of this license by one of the following three methods:

- 1) Upload a scanned copy of the document as a pdf on the JoVE submission site;
- 2) Fax the document to +1.866.381.2236;
- 3) Mail the document to JoVE / Attn: JoVE Editorial / 1 Alewife Center #200 / Cambridge, MA 02139

For questions, please email submissions@jove.com or call +1.617.945.9051

Dear Dr. Alisha DSouza,

Thank you very much for your comments and suggestions. As you suggested, we added an additional figure with photographs as well as detailed explanations about the dimensions of the set up. In addition, we addressed all the in text comments and reformulated the manuscript where needed.

If you have further comments or suggestions, I am at your disposal.

Sincerely,

Mark Douvidzon

RE: Case #00473955 - Reprint Permission of Figures [
ref:_00D30oeGz._5000c1WYUBy:ref]

Journalpermissions <journalpermissions@springernature.com>

Mo 19.03.2018 17:14

An: Mark Douvidzon <mark.douvidzon@campus.technion.ac.il>;

Dear Mark,

Thank you for your email. This work is licensed under a Creative Commons Attribution 4.0 International License, which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. **You are not required to obtain permission to reuse this article.** The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in the credit line; if the material is not included under the Creative Commons license, users will need to obtain permission from the license holder to reproduce the material. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

Kind regards,
Oda

Oda Siqveland
Permissions Assistant

SpringerNature
The Campus, 4 Crinan Street, London N1 9XW,
United Kingdom
T +44 (0) 207 014 6851

<http://www.nature.com>
<http://www.springer.com>
<http://www.palgrave.com>

From: mark.douvidzon@campus.technion.ac.il [mailto:mark.douvidzon@campus.technion.ac.il]
Sent: 18 March 2018 11:16
To: Permissions@nature.com
Subject: WG: Case #00473955 - Reprint Permission of Figures [ref:_00D30oeGz._5000c1WYUBy:ref]

Dear Sir, Madam,
I am the author of the below mentioned article. Could you please issue me an official document that permission is granted to reuse the article if cited correctly?
Thank you very much.
Best Regards,
Mark Douvidzon

Von: noreply@salesforce.com <noreply@salesforce.com> im Auftrag von customercare@copyright.com
<customercare@copyright.com>
Gesendet: Freitag, 16. März 2018 04:26

An: Mark Douvidzon

Betreff: Case #00473955 - Reprint Permission of Figures [ref:_00D30oeGz._5000c1WYUBy:ref]

Dear Mark Douvidzon,

Good day! Welcome to the RightsLink service of Copyright Clearance Center.

Please be advised that "**Light and Capillary Waves Propagation in Water Fibers**" is an Open Access article licensed under the terms of the [Creative Commons CC BY](#). This allows you to reuse the article provided that the authors and original source of publication are properly cited.

If you need a formal document stating that permission is granted to reuse the material or want to get more information, kindly contact the publisher directly at:

permissions@nature.com

If you have any further questions please don't hesitate to contact a Customer Account Specialist at 855-239-3415 Monday-Friday, 24 hours/day.

Best regards,

Rose Cabudoc
Customer Account Specialist
Copyright Clearance Center
222 Rosewood Drive
Danvers, MA 01923
www.copyright.com
+1.855.239.3415

[Facebook](#) - [Twitter](#) - [LinkedIn](#)

ref:_00D30oeGz._5000c1WYUBy:ref

----- Original Message -----

From: mark.douvidzon@campus.technion.ac.il [mark.douvidzon@campus.technion.ac.il]

Sent: 3/15/2018 12:36 PM

To: customercare@copyright.com

Subject: Reprint Permission of Figures

Dear Sir, Madam,

I am the author of an article published in "Scientific Reports", with the title : "Light and Capillary Waves Propagation in Water Fibers" (<https://www.nature.com/articles/s41598-017-16906-0>). I would like to reproduce the figure in the above named paper for a different publication. Could you please explain to me, the steps I need to undertake to be able to do so? Obviously, I would cite the Scientific Reports in my figure caption.

Sincerely,
Mark Douvidzon

3/20/2018

E-Mail – mark.douvidzon@campus.technion.ac.il

ref:_00D30oeGz._5000c1WYUBy:ref